

Source Water Assessment

A Hydrogeologic Susceptibility and Vulnerability Assessment for Holy Spirit Center - Well 2 Public Drinking Water System, Anchorage, Alaska PWSID # 218651.002

DRINKING WATER PROTECTION REPORT 1615

Alaska Department of Environmental Conservation

January, 2009

Source Water Assessment for Holy Spirit Center - Well 2 Public Drinking Water System Anchorage, Alaska PWSID# 218651.002

DRINKING WATER PROTECTION REPORT 1615

The Drinking Water Protection (DWP) section of the Drinking Water Program is producing Source Water Assessments in compliance with the Safe Drinking Water Act Amendments of 1996. Each assessment includes a delineation of the source water area, an inventory of potential and existing contaminant sources that may impact the water, a risk ranking for each of these contaminants, and an evaluation of the potential vulnerability of these drinking water sources.

These assessments are intended to provide public water systems owners/operators, communities, and local governments with the best available information that may be used to protect the quality of their drinking water. The assessments combine information obtained from various sources, including the U.S. Environmental Protection Agency, Alaska Department of Environmental Conservation (DEC), public water system owners/operators, and other public information sources. The results of this assessment are subject to change if additional data becomes available. It is anticipated this assessment will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of public drinking water source. If you have any additional information that may affect the results of this assessment, please contact the DWP staff at the following toll-free number 1-866-956-7656.

January, 2009

CONTENTS

Page	
Executive Summary1	Ranking of Contaminant Risks2
Holy Spirit Center - Well 2 Public Drinking Water	Vulnerability of Holy Spirit Center - Well 2 Drinking
System 1	Water System2
Holy Spirit Center - Well 2 Drinking Water Protection	References5
Area 1	Appendix A7
Inventory of Potential and Existing Contaminant	Appendix B9
Sources	Appendix C11

TABLES

Table 1.	Definition of Zones	.2
Table 2.	Susceptibility	.3
Table 3.	Contaminant Risks	.3
Table 4	Overall Vulnerability	3
14010		

APPENDICES

APPENDIX

X A. Holy Spirit Center - Well 2 Drinking Water Protection Area (Map A)

- B. Contaminant Source Inventory for Holy Spirit Center Well 2 (Table 1) Contaminant Source Inventory and Risk Ranking for Holy Spirit Center - Well 2 – Bacteria and Viruses (Table 2) Contaminant Source Inventory and Risk Ranking for Holy Spirit Center - Well 2 – Nitrates/Nitrites (Table 3) Contaminant Source Inventory and Risk Ranking for Holy Spirit Center - Well 2 – Volatile Organic Chemicals (Table 4)
- C. Holy Spirit Center Well 2 Drinking Water Protection Area and Potential and Existing Contaminant Sources (Map C)

Source Water Assessment for Holy Spirit Center - Well 2 Source of Public Drinking Water, Anchorage, Alaska

Drinking Water Protection Alaska Department of Environmental Conservation

EXECUTIVE SUMMARY

The public water system for the Holy Spirit Center is a Class B (transient/non-community) water system consisting of three wells located in east Anchorage, Alaska. This report applies only to Well 2 (PWSID 218651.002). The wellhead received a susceptibility rating of Low and the aquifer received a susceptibility rating of Low. Combining these two ratings produces a Low rating for the natural susceptibility of the well. Identified potential and current sources of contaminants for Holy Spirit Center - Well 2 public drinking water source include: assumed septic systems, assumed heating oil tanks, roads, and an oil/gas pipeline. These identified potential and existing sources of contamination are considered sources of bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals. Overall, the public water source for Holy Spirit Center - Well 2 received a vulnerability rating of Low for bacteria and viruses, Low for nitrates and nitrites, and Medium for volatile organic chemicals. This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of the Holy Spirit Center to protect public health.

HOLY SPIRIT CENTER - WELL 2 PUBLIC DRINKING WATER SYSTEM

The Holy Spirit Center public water system is a Class B (transient/non-community) water system. The system consists of three wells located on the corner of O'Malley Road and Hillside Drive in Anchorage, Alaska (see Map A in Appendix A). This report applies only to Well 2 (PWSID 218651.002).

Anchorage and its surrounding communities are located in Southcentral Alaska at the head of Cook Inlet. The municipality's current population is 283,938 making it the most populated city in the state (ADCCED, 2009). Communities located within the municipality include: Anchorage, Eagle River, Chugiak, Eklutna, and Girdwood.

The majority of homes in Anchorage are connected to Anchorage Water and Wastewater Utility, providing water and sewerage (ADCCED, 2009). Natural gas is available to most homes through ENSTAR Natural Gas Company. Refuse is transported to the Anchorage Regional Landfill on Hiland Road (ADCCED, 2009).

According to the well log, Well 2 extends approximately 234 feet below the ground surface and is completed in a confined aquifer. This system operates continuously and serves six residents and twenty nonresidents through seven service connections.

HOLY SPIRIT CENTER - WELL 2 DRINKING WATER PROTECTION AREA

In order to evaluate whether a drinking water source is at risk, we must first evaluate what are the most likely pathways for surface contamination to reach the groundwater. These areas are determined by looking at the characteristics of the soil, groundwater, aquifer, and well.

The most probable area for contamination to reach the drinking water well is the drinking water protection area. The drinking water protection area is the area circling the well (the area influenced by pumping) and also the area upgradient of the well, usually forming a parabola shape. Because releases of contaminants within the protection area are most likely to impact the well, this area will serve as the focus for voluntary protection efforts.

There are many different methods for calculating the size of protection areas. Drinking Water Protection (DWP) uses a combination of two simple groundwater flow equations, the Thiem and uniform flow equations for all groundwater wells screened in unconsolidated material. The orientation of the protection zone is then drawn using a water table elevation map (if available) or a land surface elevation map of the area. The protection zone calculated by DWP is an estimate using the available information and resources, and may differ slightly from the actual capture zone. Because of uncertainties and changing site conditions, a factor of safety is added to the protection zone to form the drinking water protection area for the well.

The parameters used to calculate the shape of this protection zone are general for the whole alluvial plain and were obtained from various United States Geological Survey (USGS) reports, area well logs, and the Groundwater textbook by Freeze and Cherry (Freeze and Cherry, 1979).

The protection areas established for wells by the DEC are usually separated into two zones, limited by the watershed. These zones correspond to differences in the time-of-travel (TOT) of the water moving through the aquifer to the well. An analytical calculation was used to determine the size and shape of the protection area. The input parameters describing the attributes of the aquifer in this calculation were adopted from the U.S. Geological Survey (Patrick, Brabets, and Glass, 1989).

The time-of-travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. The following is a summary of the two protection area zones for wells and the calculated time-of-travel for each:

Table 1. Definition of Zones

Zone	Definition
А	Several months time-of-travel
В	Less than the 2 year time-of-travel

The drinking water protection area for Holy Spirit Center - Well 2 was determined using an analytical calculation and includes Zones A and B (See Map A of Appendix A).

INVENTORY OF POTENTIAL AND EXISTING CONTAMINANT SOURCES

DWP has completed an inventory of potential and existing sources of contamination within the Holy Spirit Center - Well 2 drinking water protection area. This inventory was completed through a search of agency records and other publicly available information. Potential sources of contamination to the drinking water aquifer include a wide range of categories and types. Potential drinking water contaminants are found within agricultural, residential, commercial, and industrial areas, but can also occur within areas that have little or no development.

For the basis of all Class B public water system assessments, the following three categories of drinking water contaminants were inventoried:

- Bacteria and viruses;
- Nitrates and/or nitrites;
- Volatile organic chemicals

The sources are displayed on Map C of Appendix C and summarized in Table 1 of Appendix B.

RANKING OF CONTAMINANT RISKS

Once the potential and existing sources of contamination have been identified, they are assigned a ranking according to what type and level of risk they represent. Ranking of contaminant risks for a "potential" or "existing" source of contamination is a function of toxicity and volumes of specific contaminants associated with that source. Rankings include:

- Low;
- Medium;
- High; and
- Very High.

Tables 2 through 4 in Appendix B contain the ranking of potential and existing sources of contamination with respect to bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals.

VULNERABILITY OF HOLY SPIRIT CENTER -WELL 2 DRINKING WATER SYSTEM

Vulnerability of a drinking water source to contamination is a combination of two factors:

- Natural Susceptibility; and
- Contaminant Risks.

A score for the Natural Susceptibility of the well is reached by considering the properties of the well and the aquifer.

> Susceptibility of the Wellhead (0-25 Points) + Susceptibility of the Aquifer (0-25 Points)

Natural Susceptibility of the Well (0-50 Points)

A ranking is assigned for the Natural Susceptibility according to the point score:

Natural Susceptibility Ratings						
40-50 pts	Very High					
30 to < 40 pts	High					
20 to < 30 pts	Medium					
< 20 pts	Low					

Factors contributing to the susceptibility of the wellhead are: whether the sanitary seal is in place, protection from flooding, and if the well casing is properly grouted.

The wellhead for the Holy Spirit Center - Well 2 received a **Low** susceptibility rating. The most recent sanitary survey (12/05/2002) indicates the well is capped with a sanitary seal and the land surface is sloped away from the well, but the well is not grouted according to DEC regulations. Sanitary seals prevent potential contaminants from entering the well while sloping of the land surface and grouting help to prevent potential contaminants from traveling down the outside of the well casing.

Factors contributing to the susceptibility of the aquifer are: whether the aquifer is confined or unconfined, whether the well is completed in unconsolidated or fractured bedrock, whether wells and bore holes are penetrating the aquifer and, if applicable, the depth and thickness of the confining layer.

The Holy Spirit Center – Well 2 system draws water from a confined aquifer that is overlain by a 25-foot thick confining layer of yellow clay. It received a **Low** susceptibility rating because of the deep nature of the aquifer and moderately thick confining. Deeper aquifers are more protected from surface contaminants while thicker confining layers provide greater protection from any contamination that does manage to penetrate to that depth.

Table 2 summarizes the Susceptibility scores and ratings for the Holy Spirit Center - Well 2 system.

Table 2. Susceptibility

	Score	Rating
Susceptibility of the	5	Low
Wellhead		
Susceptibility of the	8	Low
Aquifer		
Natural Susceptibility	13	Low

Contaminant risks are derived from an evaluation of the routine sampling results of the water system and the presence of potential sources of contamination. Contaminant risks to a drinking water source depend on the type and distribution of contaminant sources. Flow charts are used to assign a point score, and ratings are assigned in the same way as for the natural susceptibility:

Contaminant Risk Ratings					
40-50 pts	Very High				
30 to < 40 pts	High				
20 to < 30 pts	Medium				
< 20 pts	Low				

Table 3 summarizes the Contaminant Risks for each category of drinking water contaminants for the Holy Spirit Center - Well 2 system.

Table 3. Contaminant Risks

Category	Score	Rating
Bacteria and Viruses	12	Low
Nitrates and/or Nitrites	22	Medium
Volatile Organic Chemicals	30	High

Finally, an overall vulnerability score is assigned for each water system by combining each of the contaminant risk scores with the natural susceptibility score:

> Natural Susceptibility (0-50 Points) + Contaminant Risks (0-50 Points) =

Vulnerability of the Drinking Water Source to Contamination (0-100 Points)

	1.	• •	1.	• .
$\Delta \sigma_{21n}$	rankings a	re assigned	according	to a point score:
ngam,	rankings a	ne assigned	according	to a point score.

Overall Vulnerability Ratings						
80-100 pts Very Hi						
60 to < 80 pts	High					
40 to < 60 pts	Medium					
< 40 pts	Low					
	80-100 pts 60 to < 80 pts 40 to < 60 pts					

Table 4 contains the overall vulnerability scores (0-100) and ratings for each of the three categories of drinking water contaminants for the Holy Spirit Center - Well 2 system. Note: scores are rounded off to the nearest five.

Table 4. Overall Vulnerability

Category	Score	Rating
Bacteria and Viruses	25	Low
Nitrates and/or Nitrites	35	Low
Volatile Organic Chemicals	45	Medium

Bacteria and Viruses

The contaminant risk for bacteria and viruses is **Low** with septic systems and roads contributing to the risk to the drinking water well.

Coliforms (a bacteria) are found naturally in the environment and although they aren't necessarily a health threat, they are an indicator of other potentially harmful bacteria in the water, more specifically, fecal coliforms and E. coli, which only come from human and animal fecal waste. Harmful bacteria can cause diarrhea, cramps, nausea, headaches, or other symptoms (EPA, 2008).

Only a small amount of bacteria and viruses are required to endanger public health. Positive samples increase the overall vulnerability of the drinking water source, indicating that the source is susceptible to bacteria and virus contamination. Bacteria and viruses have not recently been detected during water sampling of the system at Holy Spirit Center - Well 2 (data reviewed in April, 2008).

After combining the contaminant risk for bacteria and viruses with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Low**.

Nitrates and Nitrites

The contaminant risk for nitrates and nitrites is **Medium** with septic systems and roads contributing to the risk to the drinking water well.

The sampling history for Holy Spirit Center - Well 2 indicates that nitrates have been detected in the water within the last 5 years, with the highest concentration of 1.94 mg/l detected on 3/21/2005 (data reviewed in April, 2008).

After combining the contaminant risk for nitrates and nitrites with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Low**.

Volatile Organic Chemicals

The contaminant risk for volatile organic chemicals is **High** with septic systems, heating oil tanks, roads, and a pipeline contributing to the risk to the drinking water well.

The drinking water at Holy Spirit Center - Well 2 has not recently been sampled for volatile organic chemicals (data reviewed in April, 2008).

After combining the contaminant risk for volatile organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Medium**.

Using the Source Water Assessment

This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of the Holy Spirit Center to protect public health. It is anticipated that Source Water Assessments will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of Holy Spirit Center - Well 2 drinking water source.


REFERENCES

- Alaska Department of Commerce, Community and Economic Development (ADCCED), Accessed 2009 [WWW document]. URL: http://www.commerce.state.ak.us/dca/commdb/CF_COMDB.htm
- Freeze, R.A. and Cherry, J.A., 1979. Groundwater. Prentice-Hall, Englewood Cliffs, NJ.
- Patrick, L.D., Brabets, T.P., and Glass, R.L., 1989, Simulation of ground-water flow at Anchorage, Alaska: US Geological Survey Water-Resources Investigations Report 88-4139, 41p.
- United States Environmental Protection Agency (EPA), Accessed 2008 [WWW document]. URL: http://www.epa.gov/safewater/contaminants/index.html.

APPENDIX A

Holy Spirit Center - Well 2 Drinking Water Protection Area Location Map (Map A)

Public Water Well System for PWS #218651.002 Holy Spirit Center Holy Spirit Center PWSID:218651.002 DEC Miles 0 0.5 1 2



Holy Spirit Center PWS 218651.002 Appendix A Map A

APPENDIX B

Contaminant Source Inventory and Risk Ranking for Holy Spirit Center - Well 2 (Tables 1-4)

Contaminant Source Inventory for HOLY SPIRIT CENTER

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	А	С	3 assumed septic systems
Tanks, heating oil, residential (above ground)	R08	R08	А	С	3 assumed heating oil tanks
Highways and roads, paved (cement or asphalt)	X20	X20	А	С	1 road
Septic systems (serves one single-family home)	R02	R02	В	С	21 assumed septic systems
Tanks, heating oil, residential (above ground)	R08	R08	В	С	21 assumed heating oil tanks
Highways and roads, paved (cement or asphalt)	X20	X20	В	С	3 roads
Pipelines (oil and gas)	X28	X28	В	С	1 gas pipeline

Page 1

Table 2

Contaminant Source Inventory and Risk Ranking for HOLY SPIRIT CENTER

PWSID 218651.002

Sources of Bacteria and Viruses

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	А	Low	С	3 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	А	Low	С	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	С	21 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	В	Low	С	3 roads

Table 3

Contaminant Source Inventory and Risk Ranking for HOLY SPIRIT CENTER

PWSID 218651.002

Sources of Nitrates/Nitrites

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	А	Low	С	3 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	А	Low	С	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	С	21 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	В	Low	С	3 roads

Table 4

Contaminant Source Inventory and Risk Ranking for HOLY SPIRIT CENTER

PWSID 218651.002


Sources of Volatile Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	А	Low	С	3 assumed septic systems
Tanks, heating oil, residential (above ground)	R08	R08	А	Medium	С	3 assumed heating oil tanks
Highways and roads, paved (cement or asphalt)	X20	X20	А	Low	С	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	С	21 assumed septic systems
Tanks, heating oil, residential (above ground)	R08	R08	В	Medium	С	21 assumed heating oil tanks
Highways and roads, paved (cement or asphalt)	X20	X20	В	Low	С	3 roads
Pipelines (oil and gas)	X28	X28	В	Medium	С	1 gas pipeline

APPENDIX C

Holy Spirit Center - Well 2 Drinking Water Protection Area and Potential and Existing Contaminant Sources (Map C)

Public Water Well System for PWS # 218651.002 Holy Spirit Center Showing Potential and Existing Sources of Contamination



			Feet
0	375	750	1,500

K	Legend
	Class B Public Water System Well
1	Groundwater Protection Zones
	Zone A Protection Area - Several Months Travel Time
	Zone B Protection Area - 2 Years Travel Time
E	
	Data Sources:
X	Contaminant Sources, Public Water System Wells, Alaska Department of Environmental Conservation (ADEC)
	All other data: Alaska Statewide Digital Mapping Initiative (SDMI)
	Drinking Water Protection Areas based on "Alaska Drinking Water Protection Program - Guidance Manual for Class B Public Water Systems" published by ADEC
	URS Corporation does not guarantee the accuracy or validity of the data provided.
E	Inset 1
- North	Anchorage Area of Map
	Holy Spirit Center

Holy Spirit Center PWS 218651.002 Appendix C Map C