



Source Water Assessment

A Hydrogeologic Susceptibility and Vulnerability Assessment for Place Bar and Motel Drinking Water System, Kenai, Alaska Place Bar and Motel PWSID # 240642.001

May 23, 2003

DRINKING WATER PROTECTION PROGRAM REPORT 480 Alaska Department of Environmental Conservation

Source Water Assessment for Place Bar and Motel Drinking Water System Kenai, Alaska Place Bar and Motel PWSID# 240642.001

DRINKING WATER PROTECTION PROGRAM REPORT 480

The Drinking Water Protection Program (DWPP) is producing Source Water Assessments in compliance with the Safe Drinking Water Act Amendments of 1996. Each assessment includes a delineation of the source water area, an inventory of potential and existing contaminant sources that may impact the water, a risk ranking for each of these contaminants, and an evaluation of the potential vulnerability of these drinking water sources.

These assessments are intended to provide public water systems owners/operators, communities, and local governments with the best available information that may be used to protect the quality of their drinking water. The assessments combine information obtained from various sources, including the U.S. Environmental Protection Agency, Alaska Department of Environmental Conservation (ADEC), public water system owners/operators, and other public information sources. The results of this assessment are subject to change if additional data becomes available. It is anticipated this assessment will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of public drinking water source. If you have any additional information that may affect the results of this assessment, please contact the Program Coordinator of DWPP, (907) 269-7521.

CONTENTS

	SUMMARY		INVENTORY OF POTENTIAL AND EXISTING	
	AND MOTEL PUBLIC I		CONTAMINANT SOURCES	
	STEM AND MOTEL DRINKIN		RANKING OF CONTAMINANT RISKS	
	ND MOTEL DRINKIN N AREA		VULNERABILITY OF THE PLACE BAR AND MOTEL DRINKING WATER SYSTEM	-
FROTECTIC	IN AREA	2	MOTEL DRINKING WATER STSTEM	
		TAB	LES	
			2	
	-		3	
			4	
Table 4. Over	all vulnerability		4	
		APPEN	DICES	
APPENDIX	A. Place Bar and Mo	otel Drinking Water	Protection Area (Map 1)	
	B. Contaminant Sour	ce Inventory for Pl	ace Bar and Motel (Table 1)	
		•	isk Ranking for Place Bar and Motel –	
		Viruses (Table 2)	'I D. I' C. Dlass Daw and Matel	
		rce inventory and R ites (Table 3)	isk Ranking for Place Bar and Motel –	
		, ,	isk Ranking for Place Bar and Motel –	
		ganic Chemicals (Ta		
	C. Place Bar and Mo	otel Drinking Water	Protection Area and Potential	
	and Existing	Contaminant Sourc	es (Map 1)	
	D. Vulnerability An	alysis for Contamin	ant Source Inventory and Risk Ranking for	
			king Water Source (Charts $1 - 8$)	

Source Water Assessment for Place Bar and Motel Source of Public Drinking Water, Kenai, Alaska

Drinking Water Protection Program Alaska Department of Environmental Conservation

EXECUTIVE SUMMARY

The public water system for the Place Bar and Motel is a Class B (transient/non-community) water system consisting of one well. The Place Bar and Motel is located at 53791 Sparrow Lane, Kenai, Alaska. The wellhead received a susceptibility rating of Low and the aquifer received a susceptibility rating of **High**. Combining these two ratings produces a **Medium** rating for the natural susceptibility of the well. Identified potential and current sources of contaminants for the Place Bar and Motel public drinking water source include: logging, and highways and roads. These identified potential and existing sources of contamination are considered as sources of bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals. Overall, the public water source for the Place Bar and Motel received a vulnerability rating of **Low** for all three contaminant categories.

PLACE BAR AND MOTEL PUBLIC DRINKING WATER SYSTEM

The Place Bar and Motel public water system (PWS) is a Class B (transient/non-community) water system. The system consists of one well located at 53791 Sparrow Lane, Kenai, Alaska (T06N, R12W, Section 11) (See Map 1 of Appendix A). Kenai is part of the Kenai Peninsula Borough, which is located directly south of the city of Anchorage (Please see the inset of Map 1 in Appendix A for location). The borough encompasses 25,600 square miles, of which only 15,700 square miles is land.

The Kenai Peninsula is broken into two distinct geographic areas; the Kenai Mountains and the Kenai Lowlands. Kenai and its surrounding communities are located in the Kenai Lowlands. Communities located within the Kenai Lowlands include Sterling, Soldotna, Kenai, Nikiski, Clam Gulch, Ninilchik, and Homer.

The Kenai Peninsula area topography varies from about 3,000 feet to 5,000 feet above sea level in the Kenai Mountains, the highest point being about 6,400 feet above sea level. The Kenai Peninsula is dotted

with many lakes and small streams, including three large lakes (Kenai Lake, Skilak Lake, and Tustemena Lake) and two substantial rivers (Kenai River, and Kasilof River) (USGS 1915).

The Place Bar and Motel water system is located within the Kenai Lowlands, which is a sub-province of the Cook Inlet-Susitna Lowland physiographic region. The Kenai Lowland is a glaciated coastal shelf situated west of the northeast-trending Kenai Mountains. Approximately 100 miles long, the coastal shelf is bordered on the west by Cook Inlet, on the east by Kenai Mountains, on the north by Turnagain Arm, and on the south by the Caribou Hills and Kachemak Bay. The following summary of regional geology and hydrogeology is based on studies by Bailey and Hogan (1995); Freethey and Scully (1980); Glass (1996); Hartman, et al. (1972); and Karlstrom (1964).

The Kenai Lowland is underlain by bedrock. Tertiary sedimentary bedrock is more than 500 feet below the city of Kenai airport, but is exposed along beach cliffs and road cuts near the southwest end of the lowland. Unconsolidated surficial deposits of Quaternary age include coastal deposits, glaciolacustrine deposits, glaciofluvial deposits, glacial moraine deposits, and periglacial wind deposits. Unconsolidated Quaternary cover on the lowlands generally thickens from south to North being thin or absent in the Homer area, and over 750 feet thick near Nikiski.

The most significant groundwater resources of the Kenai Lowlands are contained in Quarternary coarse-grained sands and gravels. Flood plain, river terrace and other alluvial deposits are common aquifer materials in the area, and are characterized by high rates of recharge, and large saturated thicknesses. Other favorable materials include proglacial lake and associated river deposits and glacial outwash deposits consisting of meltwater sorted sand and gravel material. Unsorted flacial moraine and drift deposits generally have poor groundwater yields, as do discontinuous layers of confining clays and silt that are common throughout the unconsolidated materials. The relatively thicker sequence of unconsolidated

sediments in the northern portions of the Kenai Lowlands locally hosts thicker, more extensive clay aquitards and multiple aquifers.

The Kenai Peninsula area has a central water system, however, many homes and businesses in the area rely on individual wells for their water supply. Most of these wells are deep with depths between 50 and 200 feet. Static water levels in many of these wells are between 10 and 30 feet below the surface. Although groundwater quality can vary significantly in short distance, groundwater supplies are abundant in the area.

According to information obtained from ADEC records for the Place Bar and Motel PWS, the depth of the well is 70 feet below ground surface (bgs), and is screened in an unconfined aquifer. The well is screened in glacial outwash primarily composed of gravel, and the static water level is approximately 47.3 feet bgs. The well is not located in a floodplain.

The Sanitary Survey (06/23/99) for the water system indicated that the land is sloped away from the well providing adequate surface water drainage. The well is not grouted according to ADEC regulations. Proper grouting provides added protection against contaminants traveling down the annulus along the well casing and into source waters.

This system operates year round and serves 2 residents and up to 25 non-residents through one service connection.

PLACE BAR AND MOTEL DRINKING WATER PROTECTION AREA

In order to evaluate whether a drinking water source is at risk, we must first evaluate what are the most likely pathways for surface contamination to reach the groundwater. These areas are determined by looking at the characteristics of the soil, groundwater, aquifer, and well.

The most probable area for contamination to reach the drinking water well is the area that contributes water to the well, the groundwater recharge area. This area is designated as the drinking water protection area (DWPA). Because releases of contaminants within the protection area are most likely to impact the drinking water well, this area will serve as the focus for voluntary protection efforts.

An analytical calculation was used to determine the size and shape of the DWPA for the Place Bar and Motel. The input parameters describing the attributes

of the aquifer in this calculation were adopted from Groundwater (*Freeze and Cherry 1979*). Available geology and groundwater contours were also considered to take into account any uncertainties in groundwater flow and aquifer characteristics to arrive at a meaningful protection area.

The protection areas established for wells by the ADEC are usually separated into four zones, limited by the watershed. These zones correspond to differences in the time-of-travel (TOT) of the water moving through the aquifer to the well (Please refer to the Guidance Manual for Class B Public Water Systems for additional information).

The time of travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. The following is a summary of the four protection area zones for wells and the calculated time -of-travel for each:

Table 1. Definition of Zones

Zone	Definition
A	½ the distance for the 2-yr. time -of-travel
В	Less than the 2 year time-of-travel
C	Less Than the 5 year time -of-travel
D	Less than the 10 year time -of-travel

The DWPA for the Place Bar and Motel was determined using an analytical calculation and includes Zone A, B, C, and D (See Map 1 of Appendix A).

INVENTORY OF POTENTIAL AND EXISTING CONTAMINANT SOURCES

The Drinking Water Protection Program has completed an inventory of potential and existing sources of contamination within the Place Bar and Motel DWPA. This inventory was completed through a search of agency records and other publicly available information. Potential sources of contamination to the drinking water aquifer include a wide range of categories and types. Potential drinking water contaminants are found within agricultural, residential, commercial, and industrial areas, but can also occur within areas that have little or no development.

For the basis of all Class B public water system assessments, three categories of drinking water contaminants were inventoried. They include:

- Bacteria and viruses;
- Nitrates and/or nitrites;
- Volatile organic chemicals

The sources are displayed on Map 1 of Appendix C and summarized in Table 1 of Appendix B.

RANKING OF CONTAMINANT RISKS

Once the potential and existing sources of contamination have been identified, they are assigned a ranking according to what type and level of risk they represent. Ranking of contaminant risks for a "potential" or "existing" source of contamination is a function of toxicity and volumes of specific contaminants associated with that source. Rankings include:

- Low;Medium;High; and
- Very High.

The time-of-travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. Bacteria and Viruses are only inventoried in Zones A and B because of their short life span. Only "Very High" and "High" rankings are inventoried within the outer Zone D due to the probability of contaminant dilution by the time the contaminants get to the well.

Tables 2 through 4 in Appendix B contain the ranking of potential and existing sources of contamination with respect to bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals.

VULNERABILITY OF THE PLACE BAR AND MOTEL DRINKING WATER SYSTEM

Vulnerability of a drinking water source to contamination is a combination of two factors:

- Natural susceptibility; and
- Contaminant risks.

Appendix D contains eight charts, which together form the 'Vulnerability Analysis' for a source water assessment for a public drinking water source. Chart 1 analyzes the 'Susceptibility of the Wellhead' to contamination by looking at the construction of the well and its surrounding area. Chart 2 analyzes the 'Susceptibility of the Aquifer' to contamination by looking at the naturally occurring attributes of the water source and influences on the groundwater system that might lead to contamination. Chart 3 analyzes 'Contaminant Risks' for the drinking water source with respect to bacteria and viruses. The 'Contaminant Risks' portion of the analysis considers potential sources of contaminants as well as a review of contamination that has or may have occurred, but has not arrived or been detected at the well. Lastly,

Chart 4 contains the 'Vulnerability Analysis for Bacteria and Viruses'. Charts 5 through 8 contain the Contaminant Risks and Vulnerability Analyses for nitrates and nitrites and volatile organic chemicals, respectively.

A score for the Natural Susceptibility is reached by considering the properties of the well and the aquifer.

Susceptibility of the Wellhead (0 – 25 Points) (Chart 1 of Appendix D)

+

Susceptibility of the Aquifer (0 – 25 Points) (Chart 2 of Appendix D)

=

Natural Susceptibility (Susceptibility of the Well) (0-50 Points)

A ranking is assigned for the Natural Susceptibility according to the point score:

Natural Susceptibility Ratings									
40 to 50 pts	Very High								
30 to < 40 pts	High								
20 to < 30 pts	Medium								
< 20 pts	Low								

The well for the Place Bar and Motel is completed in an unconfined aquifer setting. Because an unconfined aquifer is recharged by surface water and precipitation that migrates downward from the surface, contaminants at the surface have the potential to adversely impact this aquifer. Table 2 shows the Susceptibility scores and ratings for the Place Bar and Motel.

Table 2. Susceptibility

	Score	Rating
Susceptibility of the	5	Low
Wellhead		
Susceptibility of the	16	High
Aquifer		
Natural Susceptibility	21	Medium

Contaminant risks to a drinking water source depend on the type, number or density, and distribution of contaminant sources. This score has been derived from an examination of existing and historical contamination that has been detected at the drinking water source through routine sampling. It also evaluates potential sources of contamination. Flow charts are used to assign a point score, and ratings are assigned in the same way as for the natural susceptibility:

Contaminant Risk Ratings								
40 to 50 pts	Very High							
30 to < 40 pts	High							
20 to < 30 pts	Medium							
< 20 pts	Low							

Table 3 summarizes the Contaminant Risks for each category of drinking water contaminants.

Table 3. Contaminant Risks

Category	Score	Rating		
Bacteria and Viruses	12	Low		
Nitrates and/or Nitrites	12	Low		
Volatile Organic Chemica	ls 12	Low		

Finally, an overall vulnerability score is assigned for each water system by combining each of the contaminant risk scores with the natural susceptibility score:

Contaminant Risks (0 – 50 points)

Drinking Water Source to Contamination (0 – 100).

= Vulnerability of the

Again, rankings are assigned according to a point score:

Overall Vulnerability Ratings								
80 to 100 pts	Very High							
60 to < 80 pts	High							
40 to < 60 pts	Medium							
< 40 pts	Low							

Table 4 contains the overall vulnerability scores (0 – 100) and ratings for each of the three categories of drinking water contaminants. Note: scores are rounded off to the nearest five.

Table 4. Overall Vulnerability

Category	Score	Rating
Bacteria and Viruses	35	Low
Nitrates and Nitrites	35	Low
Volatile Organic Chemicals	35	Low

Bacteria and Viruses

The contaminant risk for bacteria and viruses is Low. This risk is primarily based on the lack of potential and inventoried contaminant sources present in Zones A and B, representing the risk to the drinking water well (See Chart 3 – Contaminant Risks for Bacteria and Viruses in Appendix D).

Only a small amount of bacteria and viruses are required to endanger public health. Bacteria and viruses have been detected, but not confirmed, during recent water sampling of the system at Place Bar and Motel. After combining the contaminant risk for bacteria and viruses with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Low**.

Nitrates and Nitrites

The contaminant risk for nitrates and nitrites is Low. The risk to this source of public drinking water is primarily attributed to the lack of potential and inventoried contaminant sources present in Zones A, B and C, and reported nitrate concentrations from recent sampling events (See Chart 5 - Contaminant Risks for Nitrates and/or Nitrites in Appendix D). Nitrates are very mobile, moving at approximately the same rate as water.

Sampling history for the Place Bar and Motel well indicates that nitrate concentrations have been reported as non-detect in recent years. Nitrate concentrations in uncontaminated groundwater are typically less than 2 mg/L, therefore, nitrate concentrations above 2 mg/L may be indicative of man-made sources. The nitrate concentration from the most recent sampling event is 0% (0.0 mg/L) of the Maximum Contaminant Level (MCL) of 10 mg/L. The MCL is the maximum level of contaminant that is allowed to exist in drinking water and still be consumed by humans without harmful health effects.

Nitrate levels are often derived from the decomposition of organic matter in soils. After combining the contaminant risk for nitrates and nitrites with the natural susceptibility of the well, the overall vulnerability of the well to nitrate and nitrite

contamination is Low.

Volatile Organic Chemicals

The contaminant risk for volatile organic chemicals is Low. The risk is primarily attributed to the lack of potential and inventoried contaminant sources present in Zones A, B and C (See Chart 7 – Contaminant Risks for Volatile Organic Chemicals in Appendix D).


The drinking water at Place Bar and Motel has not been sampled for volatile organic chemicals. After combining the contaminant risk for volatile organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Low**.

REFERENCES

- Alaska Department of Community and Economic Development (ADCED), 2002 [WWW document]. URL http://www.dced.state.ak.us/mra/CF_BLOCK.cfm.
- Alaska Department of Environmental Conservation, Contaminated Sites Database, 2003 [WWW database], URL http://www.state.ak.us/dec/dspar/csites/cs_search.htm
- Alaska Department of Environmental Conservation, Leaking Underground Storage Tank Database, 2003 [WWW database], URL http://www.dec.state.ak.us/spar/stp/ust/search/fac_search.asp
- Bailey, B.J., and Hogan, E.V., 1995Overview of environmental and hydrogeologic conditions near Kenai, Alaska. U.S. Geological Survey Open-File Report 95-410, 18 p.
- Freethey, G.W., and Scully, D.R. 1980 Water Resources of the Cook Inlet Basin, Alaska. U.S. Geological Survey Hydrologic Investigation Atlas HA-620, prepared in cooperation with Alaska Water Study Committee, State of Alaska Department of Natural Resources, and Division of Geological and Geophysical Surveys.
- Freeze, R. A., and Cherry, J.A. 1979, Groundwater, Prentice-Hall, Englewood Cliffs, New Jersey
- Glass, Roy, L. 1996 Groundwater Conditions and Quality in the Western Part of the Kenai Peninsula, Southcentral Alaska. U.S. Geological Survey Open File Report 94-466, prepared in cooperation with the Alaska Department of Natural Resources, Kenai Peninsula Borough, and Kenai Soil and Water Conservation District.
- Hartman, D.C., Pessel, G.H., and McGee, D.I., 1972 Kenai Group of Cook Inlet Basin, Alaska: State of Alaska. Open File Report #49, Department of Natural Resources Division of Geological and Geophysical Surveys, 5p.
- Karlstrom, T.N.V. 1964 Quaternary geology of the Kenai Lowland and glacial history of the Cook Inlet region, Alaska. U.S. Geological Survey Professional Paper 443, 64 p.
- Kenai River Watershed, 2002 [WWW document]. URL http://www.kenai-watershed.org/spawning/kenai-river/kenai-river.html.
- Martin, G.C., Johnson, B.L., and Grant, 1915, Geology and mineral resources of Kenai Peninsula, Alaska: US Geological Survey Bulletin 587, 243 p., maps.
- United States Environmental Protection Agency (EPA), 2002 [WWW document]. URL http://www.epa.gov/safewater/mcl.html.

APPENDIX A

Place Bar and Motel Drinking Water Protection Area Location Map (Map 1)



APPENDIX B

Contaminant Source Inventory and Risk Ranking for Place Bar and Motel (Tables 1-4)

Contaminant Source Inventory for Place Bar and Motel

Contaminant Source ID	CS ID tag	Zone	Map Number	Comments
R01	R01-01	A	1	0.51 acres of residential area located in Zone A
X20	X20-01	A	1	Kenai Spur Road
X20	X20-02	A	1	Sparrow Lane
R01	R01-02	В	1	4.54 acres of residential area located in Zone B
E02	E02-01	С	1	Past and present logging - Prospect Heights Corporation
R01	R01-03	С	1	7.1 acres of residential area located in Zone C
X20	X20-03	С	1	Unnamed road
	R01 X20 X20 R01 E02 R01	Source ID CS ID tag R01 R01-01 X20 X20-01 X20 X20-02 R01 R01-02 E02 E02-01 R01 R01-03	Source ID CS ID tag Zone R01 R01-01 A X20 X20-01 A X20 X20-02 A R01 R01-02 B E02 E02-01 C R01 R01-03 C	Source ID CS ID tag Zone Map Number R01 R01-01 A 1 X20 X20-01 A 1 X20 X20-02 A 1 R01 R01-02 B 1 E02 E02-01 C 1 R01 R01-03 C 1

Contaminant Source Inventory and Risk Ranking for Place Bar and Motel Sources of Bacteria and Viruses

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Residential Areas	R01	R01-01	A	Low	1	0.51 acres of residential area located in Zone A
Highways and roads, paved (cement or asphalt)	X20	X20-01	A	Low	1	Kenai Spur Road
Highways and roads, paved (cement or asphalt)	X20	X20-02	A	Low	1	Sparrow Lane
Residential Areas	R01	R01-02	В	Low	1	4.54 acres of residential area located in Zone B

Contaminant Source Inventory and Risk Ranking for Place Bar and Motel Sources of Nitrates/Nitrites


Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Residential Areas	R01	R01-01	A	Low	1	0.51 acres of residential area located in Zone A
Highways and roads, paved (cement or asphalt)	X20	X20-01	A	Low	1	Kenai Spur Road
Highways and roads, paved (cement or asphalt)	X20	X20-02	A	Low	1	Sparrow Lane
Residential Areas	R01	R01-02	В	Low	1	4.54 acres of residential area located in Zone B
Logging (active)	E02	E02-01	С	Low	1	Past and present logging - Prospect Heights Corporation
Residential Areas	R01	R01-03	С	Low	1	7.1 acres of residential area located in Zone C
Highways and roads, paved (cement or asphalt)	X20	X20-03	С	Low	1	Unnamed road

Contaminant Source Inventory and Risk Ranking for Place Bar and Motel Sources of Volatile Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Residential Areas	R01	R01-01	A	Low	1	0.51 acres of residential area located in Zone A
Highways and roads, paved (cement or asphalt)	X20	X20-01	A	Low	1	Kenai Spur Road
Highways and roads, paved (cement or asphalt)	X20	X20-02	A	Low	1	Sparrow Lane
Residential Areas	R01	R01-02	В	Low	1	4.54 acres of residential area located in Zone B
Logging (active)	E02	E02-01	С	Low	1	Past and present logging - Prospect Heights Corporation
Residential Areas	R01	R01-03	С	Low	1	7.1 acres of residential area located in Zone C
Highways and roads, paved (cement or asphalt)	X20	X20-03	С	Low	1	Unnamed road

APPENDIX C

Place Bar and Motel
Drinking Water Protection Area
and Potential and Existing Contaminant Sources
(Map 1)



APPENDIX D

Vulnerability Analysis for Place Bar and Motel Public Drinking Water Source (Charts 1-8)

Chart 1. Susceptibility of the wellhead - Place Bar and Motel (240642.001) Susceptibility initially assumed to be low. Susceptibility of wellhead = 0 ptsNO Is the well Increase susceptibility 5 pts + 5 pts properly grouted? Is the well Increase susceptibility 20 pts + 0 pts capped? Unknown if well is grouted; assumed no based on well construction date - 1/1/1973 YES YES Susceptibility of wellhead Low 5 pts YES Increase susceptibility: Is the well 10 pts: suspected floodplain 0 pts within a Wellhead Susceptibility Ratings floodplain? 20 pts: known floodplain 20 to 25 pts very high 15 to < 20 pts high 10 to < 15 pts medium NO < 10 pts Is the land surface sloped Increase susceptibility 5 pts 0 pts away from the well?

Page 1 of 13

Chart 2. Susceptibility of the aquifer - Place Bar and Motel (240642.001)







Chart 3. Contaminant risks for Place Bar and Motel (240642.001) - Bacteria & Viruses








Contaminant risks initially assumed to be low. Current level of Evaluate the level of Contaminant risks contamination due to manbackground = 0 ptscontamination from made source(s) natural sources 0 pts NO or Is the concentration of Has nitrates and/or UNKNOWN the contaminant nitrites been detected in increasing, decreasing, the source waters in or staying the same? recent sampling period(s)? Recent Nitrate Sampling Results (mg/L) 6/5/2001 9/13/2000 ND 9/17/1999 ND ND 8/9/1998 Increasing: risk up 1 - 10 pts YES ND 8/12/1997 Decreasing: risk down 1 - 5 pts + 0 pts Same: risk unchanged Maximum Contaminant Level (MCL) = 10 mg/LDetected Nitrate Level = Existing contamination points based on Risk due to existing man-Risk due to natural linear interpolation of most recent detect made sources sources [MCL = 50 pts; detect = 0 pts]0 pts 0 pts Risk due to existing contamination 0 pts Was the source of Evaluate the level of NO. contamination contamination from natural? man-made sources YES

Chart 5. Contaminant risks for Place Bar and Motel (240642.001) - Nitrates and Nitrites




What level of risk is associated with the highest and the next highest risk sources(s) of contaminants identified in Zones A, B and C?

isk Levels for Contaminant Sources identified in Zones A, B and C						
	Zone A	Zones B&C	Total			
Very Highs(s)	0	0	0			
High(s)	0	0	0			
Medium(s)	0	0	0			
Low(s)	2	4	6			

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score 10

Note: Septic systems, sewerlines, and roads are each assigned a risk ranking for each individual contaminant source in the CSI. The VA, however, counts these contaminant sources as a group and assigns a calculated number of either "lows" or "mediums" based on the density.








Chart 6. Vulnerability analysis for Place Bar and Motel (240642.001) - Nitrates and Nitrites (Chart 1. Susceptibiltiy of the wellhead) Susceptibility of well Medium 21 pts Evaluate the susceptibility of the wellhead (Chart 5. Contaminant risks for wells - Nitrates and Nitrites) Evaluate contaminant Susceptibility of wellhead Low risks Evaluate the Contaminant risks (Chart 2. Susceptibility of the aquifer) Low susceptibility of the aquifer within the protection area Susceptibility of aquifer High Susceptibility of the well Contaminant risks Vulnerability of drinking water well to contamination Susceptibility of the wellhead Overall Vulnerability Ratings Susceptibility of aquifer 80 to 100 pts very high 60 to < 80 pts high Susceptibility of well Vulnerability of drinking water 40 to < 60 pts medium well < 40 pts 33 pts Low

Page 9 of 13

35








Chart 8. Vulnerability analysis for Place Bar and Motel (240642.001) - Volatile Organic Chemicals (Chart 1. Susceptibiltiy of the wellhead) Susceptibility of well Medium 21 pts Evaluate the susceptibility of the wellhead (Chart 7. Contaminant risks for wells - Volatile Organic Chemicals) Evaluate contaminant Susceptibility of wellhead Low risks Evaluate the Contaminant risks (Chart 2. Susceptibility of the aquifer) Low susceptibility of the aquifer within the protection area Susceptibility of aquifer High Susceptibility of the well Contaminant risks Vulnerability of drinking water well to contamination Susceptibility of the wellhead Overall Vulnerability Ratings Susceptibility of aquifer 80 to 100 pts very high 60 to < 80 pts high Susceptibility of well Vulnerability of drinking water 40 to < 60 pts medium well < 40 pts 33 pts Low **35**

Page 13 of 13