



Source Water Assessment

A Hydrogeologic Susceptibility and Vulnerability Assessment for Tesoro Alaska Petroleum Refinery Drinking Water System, Nikiski area, Alaska PWSID 241745.001

January 2004

DRINKING WATER PROTECTION PROGRAM REPORT 1300 Alaska Department of Environmental Conservation

Source Water Assessment for Tesoro Alaska Petroleum Refinery Drinking Water System Nikiski area, Alaska PWSID 241745.001

January 2004

DRINKING WATER PROTECTION PROGRAM REPORT 1300

The Drinking Water Protection Program (DWPP) is producing Source Water Assessments in compliance with the Safe Drinking Water Act Amendments of 1996. Each assessment includes a delineation of the source water area, an inventory of potential and existing contaminant sources that may impact the water, a risk ranking for each of these contaminants, and an evaluation of the potential vulnerability of these drinking water sources.

These assessments are intended to provide public water systems owners/operators, communities, and local governments with the best available information that may be used to protect the quality of their drinking water. The assessments combine information obtained from various sources, including the U.S. Environmental Protection Agency, Alaska Department of Environmental Conservation (ADEC), public water system owners/operators, and other public information sources. The results of this assessment are subject to change if additional data becomes available. It is anticipated this assessment will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of public drinking water source. If you have any additional information that may affect the results of this assessment, please contact the Program Coordinator of DWPP, (907) 269-7521.

Page

2 2

3 7

			CONT	ENTS	
Executive Summary Tesoro Refinery Public Drinking Water System Tesoro Refinery Protection Area		Water System	Page 1 1	Inventory of Potential and Existing Contaminant Sources Ranking of Contaminant Risks Vulnerability of Tesoro Refinery Drinking Water System References	
			TAB	LES	
TABLE	1.	Definition of Zones			2
	2. 3. 3.	Susceptibility Contaminant Risks Overall Vulnerability			3 4 4
		1	APPEN	DICES	
APPENDIX	A.	Tesoro Refinery Drinking	Water Pro	otection Area (Map 1)	
	В.	Bacteria and Viruses Contaminant Source Inve Nitrates/Nitrites (Tak Contaminant Source Inve Volatile Organic Che Contaminant Source Inve Heavy Metals, Cyani Contaminant Source Inve Synthetic Organic Cl	ntory and I (Table 2) ntory and I ble 3) ntory and I emicals (Ta ntory and I de, and Ot entory and nemicals (I ntory and I	Risk Ranking for Tesoro Refinery— Risk Ranking for Tesoro Refinery— Risk Ranking for Tesoro Refinery— Able 4) Risk Ranking for Tesoro Refinery— her Inorganic Chemicals (Table 5) Risk Ranking for Tesoro Refinery— Fiable 6) Risk Ranking for Tesoro Refinery— Risk Ranking for Tesoro Refinery—	
	C.	Tesoro Refinery Drinking and Existing Contam			

D. Vulnerability Analysis for Contaminant Source Inventory and Risk Ranking for Tesoro Refinery Public Drinking Water Source (Charts 1-14)

Source Water Assessment for Tesoro Refinery Source of Public Drinking Water, Nikiski area, Alaska

Drinking Water Protection Program Alaska Department of Environmental Conservation

EXECUTIVE SUMMARY

The public water system for Tesoro Refinery is a Class A (non-transient/non-community) water system consisting of two wells. This report looks at The Tesoro Refinery. The well is located off of the Kenai Spur Highway. The wellhead received a susceptibility rating of Low and the aquifer received a susceptibility rating of **Medium**. Combining these two ratings produces a **Low** rating for the natural susceptibility of the well. Identified potential and current sources of contaminants for the Tesoro Refinery include: roads and parking lot. These identified potential and existing sources of contamination are considered as sources of bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals, inorganic chemicals and other organic chemicals. Overall, the public water source for the Tesoro Refinery received a vulnerability rating of Low for bacteria and viruses, nitrates and nitrites, synthetic organic chemicals, other organic chemicals and volatile organic chemicals and High for inorganic chemicals

TESORO REFINERYPUBLIC DRINKING WATER SYSTEM

The Tesoro Refinery public water system (PWS) is a Class A (non-transient/non-community) water system. The system consists of one well. The Tesoro Refinery is located off of the Kenai Spur Highway. (See Map 1 of Appendix A). Nikiski is part of the Kenai Peninsula Borough, which is located directly south of the city of Anchorage (Please see the inset of Map 1 in Appendix A for location). The borough encompasses 25,600 square miles, of which only 15,700 square miles is land.

The Kenai Peninsula is broken into two distinct geographic areas; the Kenai Mountains and the Kenai Lowlands. Nikiski and its surrounding communities are located in the Kenai Lowlands. Communities located within the Kenai Lowlands include Sterling, Soldotna, Kenai, Nikiski, Clam Gulch, Ninilchik, and Homer.

The Kenai Peninsula area topography varies from about 3,000 feet to 5,000 feet above sea level in the Kenai Mountains, the highest point being about 6,400 feet above sea level. The Kenai Peninsula is dotted with many lakes and small streams, including three large lakes (Kenai Lake, Skilak Lake, and Tustemena Lake)

and two substantial rivers (Kenai River, and Kasilof River) (USGS 1915).

The Tesoro Refinery water system is located within the Kenai Lowlands, which is a sub-province of the Cook Inlet-Susitna Lowland physiographic region. The Kenai Lowland is a glaciated coastal shelf situated west of the northeast-trending Kenai Mountains. Approximately 100 miles long, the coastal shelf is bordered on the west by Cook Inlet, on the east by Kenai Mountains, on the north by Turnagain Arm, and on the south by the Caribou Hills and Kachemak Bay. The following summary of regional geology and hydrogeology is based on studies by Bailey and Hogan (1995); Freethey and Scully (1980); Glass (1996); Hartman, et al. (1972); and Karlstrom (1964).

The Kenai Lowland is underlain by bedrock. Tertiary sedimentary bedrock is more than 500 feet below the city of Kenai airport, but is exposed along beach cliffs and road cuts near the southwest end of the lowland. Unconsolidated surficial deposits of Quaternary age include coastal deposits, glaciolacustrine deposits, glaciofluvial deposits, glacial moraine deposits, and periglacial wind deposits. Unconsolidated Quaternary cover on the lowlands generally thickens from south to North being thin or absent in the Homer area, and over 750 feet thick near Nikiski.

The most significant groundwater resources of the Kenai Lowlands are contained in Quarternary coarsegrained sands and gravels. Flood plain, river terrace and other alluvial deposits are common aquifer materials in the area, and are characterized by high rates of recharge, and large saturated thicknesses. Other favorable materials include proglacial lake and associated river deposits and glacial outwash deposits consisting of meltwater sorted sand and gravel material. Unsorted glacial moraine and drift deposits generally have poor groundwater yields, as do discontinuous layers of confining clays and silt that are common throughout the unconsolidated materials. The relatively thicker sequence of unconsolidated sediments in the northern portions of the Kenai Lowlands locally hosts thicker, more extensive clay aguitards and multiple aguifers.

The Kenai Peninsula area has a central water system, however, many homes and businesses in the area rely on individual wells for their water supply. Most of

these wells are deep with depths between 50 and 200 feet. Static water levels in many of these wells are between 10 and 30 feet below the surface. Although groundwater quality can vary significantly in short distance, groundwater supplies are abundant in the area.

According to the well log, the well is 136 feet below ground surface (bgs) and penetrates an 18 foot clay confining layer from 88-108 feet bgs. The static water level at the time of drilling (1987) was 68 feet bgs.

The Sanitary Survey (11/29/01) indicates that the well is properly sealed. A properly installed sanitary seal may provide protection against contaminant from entering the source waters at the casing. The well is not located in a floodplain and the surface is sloped away from the wellhead. Since the well was drilled in 1987, prior to grouting regulations, it is assumed that the well is not grouted. Proper grouting provides added protection against contaminants traveling along the well casing and into source waters.

This system operates year round and serves up to 140 non-residents through 12 service connections.

.

TESORO REFINERYDRINKING WATER PROTECTION AREA

In order to evaluate whether a drinking water source is at risk, we must first evaluate what are the most likely pathways for surface contamination to reach the groundwater. These areas are determined by looking at the characteristics of the soil, groundwater, aquifer, and well.

The most probable area for contamination to reach the drinking water well is the area that contributes water to the well, the groundwater recharge area. This area is designated as the drinking water protection area (DWPA). Because releases of contaminants within the protection area are most likely to impact the drinking water well, this area will serve as the focus for voluntary protection efforts.

An analytical calculation was used to determine the size and shape of the DWPA for Tesoro Refinery. The input parameters describing the attributes of the aquifer in this calculation were adopted from Groundwater (*Freeze and Cherry 1979*). Available geology and groundwater contours were also considered to take into account any uncertainties in groundwater flow and aquifer characteristics to arrive at a meaningful protection area.

The protection areas established for wells by the ADEC are usually separated into four zones, limited by the watershed. These zones correspond to differences in

the time-of-travel (TOT) of the water moving through the aquifer to the well (Please refer to the Guidance Manual for Class APublic Water Systems for additional information).

The time of travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. The following is a summary of the four protection area zones for wells and the calculated time-of-travel for each:

Table 1. Definition of Zones

Zone A B	Definition 1/4 the distance for the 2-yr. time-of-travel Less than 2 years time-of-travel
C	Less than 5 years time-of-travel
D	Less than 10 years time-of-travel

The DWPA for the Tesoro Refinery was determined using an analytical calculation and includes Zone A, B, C, and D (See Map 1 of Appendix A).

INVENTORY OF POTENTIAL AND EXISTING CONTAMINANT SOURCES

The Drinking Water Protection Program has completed an inventory of potential and existing sources of contamination within the Tesoro Refinery DWPA. This inventory was completed through a search of agency records and other publicly available information. Potential sources of contamination to the drinking water aquifer include a wide range of categories and types. Potential drinking water contaminants are found within agricultural, residential, commercial, and industrial areas, but can also occur within areas that have little or no development.

For the basis of all Class A public water system assessments, six categories of drinking water contaminants were inventoried. They include:

- Bacteria and viruses;
- Nitrates and/or nitrites;
- Volatile organic chemicals;
- Heavy metals, cyanide, and other inorganic chemicals:
- Synthetic organic chemicals; and
- Other organic chemicals.

The sources are displayed on Map 1 of Appendix C and summarized in Table 1 of Appendix B.

RANKING OF CONTAMINANT RISKS

Once the potential and existing sources of contamination have been identified, they are assigned a ranking according to what type and level of risk they represent. Ranking of contaminant risks for a "potential" or "existing" source of contamination is a function of toxicity and volumes of specific contaminants associated with that source. Rankings include:

Low;Medium;High; andVery High.

The time-of-travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. Bacteria and Viruses are only inventoried in Zones A and B because of their short life span. Only "Very High" and "High" rankings are inventoried within the outer Zone D due to the probability of contaminant dilution by the time the contaminants get to the well.

Tables 2 through 4 in Appendix B contain the ranking of potential and existing sources of contamination with respect to bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals.

VULNERABILITY OF TESORO REFINERYDRINKING WATER SYSTEM

Vulnerability of a drinking water source to contamination is a combination of two factors:

- Natural susceptibility; and
- Contaminant risks.

Appendix D contains eight charts, which together form the 'Vulnerability Analysis' for a source water assessment for a public drinking water source. Chart 1 analyzes the 'Susceptibility of the Wellhead' to contamination by looking at the construction of the well and its surrounding area. Chart 2 analyzes the 'Susceptibility of the Aquifer' to contamination by looking at the naturally occurring attributes of the water source and influences on the groundwater system that might lead to contamination. Chart 3 analyzes 'Contaminant Risks' for the drinking water source with respect to bacteria and viruses. The 'Contaminant Risks' portion of the analysis considers potential sources of contaminants as well as a review of contamination that has or may have occurred, but has not arrived or been detected at the well. Lastly, Chart 4 contains the 'Vulnerability Analysis for Bacteria and Viruses'. Charts 5 through 8 contain the Contaminant Risks and Vulnerability Analyses for nitrates and nitrites and volatile organic chemicals, respectively.

A score for the Natural Susceptibility is reached by considering the properties of the well and the aquifer.

Susceptibility of the Wellhead (0 – 25 Points) (Chart 1 of Appendix D)

+

Susceptibility of the Aquifer (0 – 25 Points) (Chart 2 of Appendix D)

=

Natural Susceptibility (Susceptibility of the Well) (0-50 Points)

A ranking is assigned for the Natural Susceptibility according to the point score:

Natural Suscept	Natural Susceptibility Ratings								
40 to 50 pts	Very High								
30 to < 40 pts	High								
20 to < 30 pts	Medium								
< 20 pts	Low								

Tesoro Refinery is completed in a confined aquifer setting. The well penetrates a confining layer and is completed in the upper confined aquifer. The confining layer may provide a protective barrier from the movement of contaminants in the subsurface. However, wells penetrating the confining layer may provide a quick path for contaminants to enter the confining aquifer. Table 2 shows the Susceptibility scores and ratings for the Tesoro Refinery.

Table 2. Susceptibility

Susceptibility of the	Score 5	Rating Low
Wellhead Susceptibility of the	10	Medium
Aquifer Natural Susceptibility	15	Low

Contaminant risks to a drinking water source depend on the type, number or density, and distribution of contaminant sources. This score has been derived from an examination of existing and historical contamination that has been detected at the drinking water source through routine sampling. It also evaluates potential sources of contamination. Flow charts are used to assign a point score, and ratings are assigned in the same way as for the natural susceptibility:

Contaminant Risk Ratings							
40 to 50 pts	Very High						
30 to < 40 pts	High						
20 to < 30 pts	Medium						
< 20 pts	Low						

Table 3 summarizes the Contaminant Risks for each category of drinking water contaminants..

Table 3. Contaminant Risks

Category	Score	Rating
Bacteria and Viruses	12	Low
Nitrates and/or Nitrites	12	Low
Volatile Organic Chemicals	23	Medium
Heavy Metals, Cyanide, and		
Other Inorganic Chemicals	50	High
Synthetic Organic Chemicals	0	Low
Other Organic Chemicals	12	Low

Finally, an overall vulnerability score is assigned for each water system by combining each of the contaminant risk scores with the natural susceptibility score:

Natural Susceptibility
$$(0 - 50 \text{ points})$$

+

Contaminant Risks (0 - 50 points)

=

Vulnerability of the Drinking Water Source to Contamination (0 - 100).

Again, rankings are assigned according to a point score:

Overall Vulnerability Ratings								
80 to 100 pts	Very High							
60 to < 80 pts	High							
40 to < 60 pts	Medium							
< 40 pts	Low							

Table 4 contains the overall vulnerability scores (0 – 100) and ratings for each of the three categories of drinking water contaminants. Note: scores are rounded off to the nearest five.

Table 4. Overall Vulnerability

Category	Score	Rating
Bacteria and Viruses	25	Low
Nitrates and Nitrites	25	Low
Volatile Organic Chemicals	35	Low
Heavy Metals, Cyanide, and		
Other Inorganic Chemicals	65	High
Synthetic Organic Chemicals	15	Low
Other Organic Chemicals	25	Low

Bacteria and Viruses

Roads represent the greatest risk for bacteria and viruses to this drinking water well.

Only a small amount of bacteria and viruses are required to endanger public health. Coli forms are found naturally in the environment and although they aren't necessarily a health threat, it is an indicator of other potentially harmful bacteria in the water, more specifically, fecal coli forms and E. coli which only come from human and animal fecal waste (EPA, 2002). Harmful bacteria can cause diarrhea, cramps, nausea, headaches, or other symptoms (EPA, 2002). Sampling has not detected bacteria within source waters.

After combining the contaminant risk for bacteria and viruses with the natural susceptibility of the well, the overall vulnerability of the well to contamination is low.

Nitrates and Nitrites

Roads represent the greatest risk to nitrates and nitrites for this source of public drinking water.

Nitrates are very mobile, moving at approximately the same rate as water. The sampling history for the well indicates that nitrate concentrations have not been detected.

After combining the contaminant risk for nitrates and nitrites with the natural susceptibility of the well, the overall vulnerability of the well to contamination is low.

Volatile Organic Chemicals

Parking lots and roads represent the greatest identified risk for volatile organic chemical contamination to the well.

Approximately 20% residents in the area typically heat their homes with various types of on-site fuel sources, including propane and heating oil stored in aboveground or underground storage tanks. Although this report does not address heating oil tanks (unless their location is known), they can pose a risk of volatile organic chemical contamination to drinking water sources. The most common causes of fuel leaks of these heating oil systems are overfilling the tank, ruptured fuel lines, leaking storage tanks, damaged or faulty valves and vandalism. Secondary containment around the tank and regular system maintenance can help prevent many of these harmful fuel leaks and help protect the drinking water supply.

Volatile Organic Chemicals have not been detected within source waters. After combining the contaminant risk for volatile organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is low.

Heavy Metals, Cyanide, and Other Inorganic Chemicals

Roads present the greatest risk for inorganic chemicals to the well.

Samplings of inorganic chemicals have detected barium, calcium, chromium, copper, iron, lead, manganese, nickel, potassium, sodium and zinc at levels below the maximum contaminant levels (MCLs). Also, arsenic was detected at levels exceeding the current MCL of 0.010 mg/l. The MCL is the maximum level of contaminant that is allowed to exist in drinking water and still be consumed by humans without harmful health effects. Further sampling of additional wells in the area indicates arsenic levels are naturally elevated. Prolonged exposure to levels exceeding the MCL can skin damage, problems with circulatory systems, and may create an increased risk of developing cancer (EPA, 2002).

After combining the contaminant risk for heavy metals, cyanide and other inorganic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is high.

Synthetic Organic Chemicals

No sources of synthetic organic chemicals have been identified within the protection area.

Sampling has not detected synthetic organic chemicals in source water.

After combining the contaminant risk for snythetic organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is low.

Other Organic Chemicals

Roads and parking lots represent the greatest risk for other organic chemicals to the well.

Sampling has not detected synthetic organic chemicals in source water.

After combining the contaminant risk for snythetic organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is low.

REFERENCES


- Alaska Department of Community and Economic Development (ADCED), 2002 [WWW document]. URL http://www.dced.state.ak.us/mra/CF_BLOCK.cfm.
- Alaska Department of Environmental Conservation, Contaminated Sites Database, 2003 [WWW database], URL http://www.state.ak.us/dec/dspar/csites/cs_search.htm
- Alaska Department of Environmental Conservation, Leaking Underground Storage Tank Database, 2003 [WWW database], URL http://www.dec.state.ak.us/spar/stp/ust/search/fac_search.asp
- Bailey, B.J., and Hogan, E.V., 1995 Overview of environmental and hydrogeologic conditions near Kenai, Alaska. U.S. Geological Survey Open-File Report 95-410, 18 p.
- Dames and Moore, 1993 Water Supply Well PW-4 Design and Installation Kenai Peninsula Borough, Kenai Alaska. Prepared for Tesoro RefineryCorporation.
- Freethey, G.W., and Scully, D.R. 1980 Water Resources of the Cook Inlet Basin, Alaska. U.S. Geological Survey Hydrologic Investigation Atlas HA-620, prepared in cooperation with Alaska Water Study Committee, State of Alaska Department of Natural Resources, and Division of Geological and Geophysical Surveys.
- Freeze, R. A., and Cherry, J.A. 1979, Groundwater, Prentice-Hall, Englewood Cliffs, New Jersey
- Glass, Roy, L. 1996 Groundwater Conditions and Quality in the Western Part of the Kenai Peninsula, Southcentral Alaska. U.S. Geological Survey Open File Report 94-466, prepared in cooperation with the Alaska Department of Natural Resources, Kenai Peninsula Borough, and Kenai Soil and Water Conservation District.
- Hartman, D.C., Pessel, G.H., and McGee, D.I., 1972 Kenai Group of Cook Inlet Basin, Alaska: State of Alaska. Open File Report #49, Department of Natural Resources Division of Geological and Geophysical Surveys, 5p.
- Karlstrom, T.N.V. 1964 Quaternary geology of the Kenai Lowland and glacial history of the Cook Inlet region, Alaska. U.S. Geological Survey Professional Paper 443, 64 p.
- Kenai River Watershed, 2002 [WWW document]. URL http://www.kenai-watershed.org/spawning/kenai-river/kenai-river.html.
- Martin, G.C., Johnson, B.L., and Grant, 1915, Geology and mineral resources of Kenai Peninsula, Alaska: US Geological Survey Bulletin 587, 243 p., maps.
- United States Environmental Protection Agency (EPA), 2002 [WWW document]. URL http://www.epa.gov/safewater/mcl.html.

ACKNOWLEDGMENT

Source Water Assessments in the Nikiski area were jointly prepared by ADEC-Drinking Water Protection Program and URS Corporation. The Drinking Water Protection Program would like to thank URS Corporation for their efforts in researching the area.

APPENDIX A

Tesoro Refinery
Drinking Water Protection Area Location Map
(Map 1)



APPENDIX B

Contaminant Source Inventory and Risk Ranking for Tesoro Refinery (Tables 1-7)

Contaminant Source Inventory for Tesoro AK Petro Co. Refinery

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Map Number	Comments
Highways and roads, paved (cement or asphalt)	X20	X20-01-3	A	2	
Highways and roads, paved (cement or asphalt)	X20	X20-04-6	A	2	
Motor vehicle/general storage yards/facilities	X27	X27-01	A	2	
Motor vehicle/general storage yards/facilities	X27	X27-02	A	2	

Contaminant Source Inventory and Risk Ranking for Tesoro AK Petro Co. Refinery Sources of Bacteria and Viruses

PWSID 241745.001

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, paved (cement or asphalt)	X20	X20-01-3	A	Low	2	
Highways and roads, paved (cement or asphalt)	X20	X20-04-6	A	Low	2	

Contaminant Source Inventory and Risk Ranking for Tesoro AK Petro Co. Refinery Sources of Nitrates/Nitrites

PWSID 241745.001

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, paved (cement or asphalt)	X20	X20-01-3	A	Low	2	
Highways and roads, paved (cement or asphalt)	X20	X20-04-6	A	Low	2	

PWSID 241745.001

Table 4

Contaminant Source Inventory and Risk Ranking for Tesoro AK Petro Co. Refinery Sources of Volatile Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, paved (cement or asphalt)	X20	X20-01-3	A	Low	2	
Highways and roads, paved (cement or asphalt)	X20	X20-04-6	A	Low	2	
Motor vehicle/general storage yards/facilities	X27	X27-01	A	Low	2	
Motor vehicle/general storage yards/facilities	X27	X27-02	A	Low	2	

Contaminant Source Inventory and Risk Ranking for Tesoro AK Petro Co. Refinery Sources of Heavy Metals, Cyanide and Other Inorganic Chemicals

PWSID 241745.001

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, paved (cement or asphalt)	X20	X20-01-3	A	Low	2	
Highways and roads, paved (cement or asphalt)	X20	X20-04-6	A	Low	2	

PWSID 241745.001


Table 6

Contaminant Source Inventory and Risk Ranking for Tesoro AK Petro Co. Refinery Sources of Other Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Highways and roads, paved (cement or asphalt)	X20	X20-01-3	A	Low	2	
Highways and roads, paved (cement or asphalt)	X20	X20-04-6	A	Low	2	
Motor vehicle/general storage yards/facilities	X27	X27-01	A	Low	2	
Motor vehicle/general storage yards/facilities	X27	X27-02	A	Low	2	

APPENDIX C

Tesoro Refinery
Drinking Water Protection Area
and Potential and Existing Contaminant Sources
(Map 2)



APPENDIX D

Vulnerability Analysis for Tesoro Refinery Public Drinking Water Source (Charts 1-14)

Chart 1. Susceptibility of the wellhead - Tesoro Alaska Petroleum Refinery PWSID 241745.001 Susceptibility initially assumed to be low. Susceptibility of wellhead = 0 pts NO Is the well Increase susceptibility 5 pts + 5 pts properly grouted? Is the well Increase susceptibility 20 pts 0 pts capped? Drilled in 1987 prior to grouting regulations. YES YES Susceptibility of wellhead Low 5 pts YES Increase susceptibility: Is the well 10 pts: suspected floodplain within a 0 pts Wellhead Susceptibility Ratings 20 pts: known floodplain floodplain? 20 to 25 pts very high 15 to < 20 pts high 10 to < 15 pts medium NO < 10 pts low Is the land surface sloped Increase susceptibility 5 pts 0 pts

away from the well?

YES

Chart 2. Susceptibility of the aquifer - Tesoro Alaska Petroleum Refinery PWSID 241745.001







Chart 3. Contaminant risks for Tesoro Alaska Petroleum Refinery PWSID 241745.001 - Bacteria & Viruses





Page 4 of 25








Chart 5. Contaminant risks for Tesoro Alaska Petroleum Refinery PWSID 241745.001 - Nitrates and Nitrites





Risk Levels for Contaminant Sources identified in Zones A, B and C							
	Zone A	Zones B&C	Total				
Very Highs(s)	0	0	0				
High(s)	0	0	0				
Medium(s)	0	0	0				
Low(s)	1	1	2				

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score 10













Chart 7. Contaminant risks for Tesoro Alaska Petroleum Refinery PWSID 241745.001 - Volatile Organic Chemicals




	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score 10












Chart 9. Contaminant risks for Tesoro Alaska Petroleum Refinery PWSID 241745.001 - Heavy Metals, Cyanide and Other Inorganic Chemicals





Risk Levels for Contaminant Sources identified in Zones A, B and C							
	Zone A	Zones B&C	Total				
Very Highs(s)	0	0	0				
High(s)	0	0	0				
Medium(s)	0	0	0				
Low(s)	1	1	2				

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score	10
--------------	----












Chart 11. Contaminant risks for Tesoro Alaska Petroleum Refinery PWSID 241745.001 - Synthetic Organic Chemicals





Risk Levels for Contaminant Sources identified in Zones A, B and C							
	Zone A	Zones B&C	Total				
Very Highs(s)	0	0	0				
High(s)	0	0	0				
Medium(s)	0	0	0				
Low(s)	0	0	0				

LOW 0 pts	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score 0











Chart 13. Contaminant risks for Tesoro Alaska Petroleum Refinery PWSID 241745.001 - Other Organic Chemicals



Risk Levels for Contaminant Sources identified in Zones A, B and C							
	Zone A	Zones B&C	Total				
Very Highs(s)	0	0	0				
High(s)	0	0	0				
Medium(s)	0	0	0				
Low(s)	3	1	4				

	LOW 10 pts	MEDIUM 20 pts	HIGH 30 pts	VERY HIGH 40 pts
LOW	≥ 10 sources + 10 pts	≥ 10 sources + 5 pts	≥ 20 sources + 5 pts	
MEDIUM		≥ 2 sources + 5 pts	≥ 5 sources + 5 pts	≥ 10 sources + 5 pts
HIGH			≥ 1 source + 10 pts	≥ 2 sources + 10 pts
VERY HIGH				≥ 1 source + 10 pts

Matrix Score 10

