

Source Water Assessment

A Hydrogeologic Susceptibility and Vulnerability Assessment for Palmer Church of Christ Public Drinking Water System, Palmer, Alaska PWSID # 227563.001

DRINKING WATER PROTECTION REPORT 1695

Alaska Department of Environmental Conservation

January, 2009

Source Water Assessment for Palmer Church of Christ Public Drinking Water System Palmer, Alaska PWSID# 227563.001

DRINKING WATER PROTECTION REPORT 1695

The Drinking Water Protection (DWP) section of the Drinking Water Program is producing Source Water Assessments in compliance with the Safe Drinking Water Act Amendments of 1996. Each assessment includes a delineation of the source water area, an inventory of potential and existing contaminant sources that may impact the water, a risk ranking for each of these contaminants, and an evaluation of the potential vulnerability of these drinking water sources.

These assessments are intended to provide public water systems owners/operators, communities, and local governments with the best available information that may be used to protect the quality of their drinking water. The assessments combine information obtained from various sources, including the U.S. Environmental Protection Agency, Alaska Department of Environmental Conservation (DEC), public water system owners/operators, and other public information sources. The results of this assessment are subject to change if additional data becomes available. It is anticipated this assessment will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of public drinking water source. If you have any additional information that may affect the results of this assessment, please contact the DWP staff at the following toll-free number 1-866-956-7656.

CONTENTS

		Page		Page
Executive Su	ımmar	y1	Ranking of Contaminant Risks	2
Palmer Chur		•	Vulnerability of Palmer Church of Christ	
Public Drink	ing W	ater System 1	Drinking Water System	2
Palmer Chur			References	5
Drinking Wa	ater Pr	otection Area1	Appendix A	7
Inventory of			Appendix B	9
		ant Sources2	Appendix C	11
		TABI	LES	
Table 1 Defin	ition o	of Zones		2.
		APPENI	DICES	
APPENDIX	A.	Palmer Church of Christ Drinking Wa	ter Protection Area (Map A)	
	В.	Viruses (Table 2) Contaminant Source Inventory and R Nitrates/Nitrites (Table 3)	mer Church of Christ (Table 1) isk Ranking for Palmer Church of Christ – Bacte isk Ranking for Palmer Church of Christ – isk Ranking for Palmer Church of Christ – Volati	
	C.	Palmer Church of Christ Drinking W Contaminant Sources (Map C)	ater Protection Area and Potential and Existing	

Source Water Assessment for

Palmer Church of Christ Source of Public Drinking Water, Palmer, Alaska

Drinking Water Protection Alaska Department of Environmental Conservation

EXECUTIVE SUMMARY

The public water system for Palmer Church of Christ is a Class B (transient/non-community) water system consisting of one well located on Scott Road in Palmer, Alaska. The wellhead received a susceptibility rating of Low and the aguifer received a susceptibility rating of Very High. Combining these two ratings produces a **High** rating for the natural susceptibility of the well. Identified potential and current sources of contaminants for Palmer Church of Christ public drinking water source include: a coal mining area, assumed septic systems, assumed heating oil tanks, and roads. These identified potential and existing sources of contamination are considered as sources of bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals. Overall, the public water sources for Palmer Church of Christ received a vulnerability rating of Medium for bacteria and viruses, Medium for nitrates and nitrites, and Very High for volatile organic chemicals. This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of Palmer Church of Christ to protect public health.

PALMER CHURCH OF CHRIST PUBLIC DRINKING WATER SYSTEM

The Palmer Church of Christ public water system is a Class B (transient/non-community) water system. The system consists of one well located on Scott Road in Palmer, Alaska (see Map A in Appendix A). Palmer is located on the Glenn Highway, approximately 42 miles northeast of Anchorage. Temperatures range from -36 to 51 in January and from 37 to 85 in July. Palmer receives an average of 16.5 inches of precipitation annually. The city has a population of 5,506 (ADCCED, 2009).

Many Palmer residents receive water that is drawn from three deep wells and stored in a million-gallon reservoir. Sewage is piped to an aerated lagoon where it is treated. Electricity is provided by Matanuska Electric Association, natural gas is provided by Enstar, and refuse is transported to a Borough-operated landfill outside of Palmer (ADCCED, 2009).

According to the well log (02/15/1983), the depth of the well is approximately 116 feet below the ground surface and is completed in an unconfined aquifer.

This system operates continuously and serves 25 to 75 non-residents once per week through one service connection.

PALMER CHURCH OF CHRIST DRINKING WATER PROTECTION AREA

In order to evaluate whether a drinking water source is at risk, we must first evaluate what are the most likely pathways for surface contamination to reach the groundwater. These areas are determined by looking at the characteristics of the soil, groundwater, aquifer, and well.

The most probable area for contamination to reach the drinking water well is the drinking water protection area. The drinking water protection area is the area circling the well (the area influenced by pumping) and also the area upgradient of the well, usually forming a parabola shape. Because releases of contaminants within the protection area are most likely to impact the well, this area will serve as the focus for voluntary protection efforts.

There are many different methods for calculating the size of protection areas. Drinking Water Protection (DWP) uses a combination of two simple groundwater flow equations, the Thiem and uniform flow equations for all groundwater wells screened in unconsolidated material. The orientation of the protection zone is then drawn using a water table elevation map (if available) or a land surface elevation map of the area. The protection zone calculated by DWP is an estimate using the available information and resources, and may differ slightly from the actual capture zone. Because of uncertainties and changing site conditions, a factor of safety is added to the protection zone to form the drinking water protection area for the well.

The parameters used to calculate the shape of this protection zone are general for the whole alluvial plain and were obtained from various United States Geological Survey (USGS) reports, area well logs, and the Groundwater textbook by Freeze and Cherry (Freeze and Cherry, 1979).

The protection areas established for wells by the DEC are usually separated into two zones, limited by the watershed. These zones correspond to differences in the time-of-travel (TOT) of the water moving through the aquifer to the well. An analytical calculation was used to determine the size and shape of the protection area. The input parameters describing the attributes of the aquifer in this calculation were adopted from the State of Alaska Department of Water Resources (Jokela *et. al.*, 1991).

The time-of-travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. The following is a summary of the two protection area zones for wells and the calculated time-of-travel for each:

Table 1. Definition of Zones

Zone	Definition								
A	Several months time-of-travel								
В	Less than the 2 year time-of-travel								

The drinking water protection area for Palmer Church of Christ was determined using an analytical calculation and includes Zones A and B (See Map A of Appendix A).

INVENTORY OF POTENTIAL AND EXISTING CONTAMINANT SOURCES

DWP has completed an inventory of potential and existing sources of contamination within the Palmer Church of Christ drinking water protection area. This inventory was completed through a search of agency records and other publicly available information. Potential sources of contamination to the drinking water aquifer include a wide range of categories and types. Potential drinking water contaminants are found within agricultural, residential, commercial, and industrial areas, but can also occur within areas that have little or no development.

For the basis of all Class B public water system assessments, the following three categories of drinking water contaminants were inventoried:

- Bacteria and viruses;
- Nitrates and/or nitrites;
- Volatile organic chemicals

The sources are displayed on Map C of Appendix C and summarized in Table 1 of Appendix B.

RANKING OF CONTAMINANT RISKS

Once the potential and existing sources of contamination have been identified, they are assigned a ranking according to what type and level of risk they represent. Ranking of contaminant risks for a "potential" or "existing" source of contamination is a function of toxicity and volumes of specific contaminants associated with that source. Rankings include:

- Low:
- Medium;
- High; and
- Very High.

Tables 2 through 4 in Appendix B contain the ranking of potential and existing sources of contamination with respect to bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals.

VULNERABILITY OF PALMER CHURCH OF CHRIST DRINKING WATER SYSTEM

Vulnerability of a drinking water source to contamination is a combination of two factors:

- Natural Susceptibility; and
- Contaminant Risks.

A score for the Natural Susceptibility of the well is reached by considering the properties of the well and the aquifer.

Susceptibility of the Wellhead (0-25 Points)

+
Susceptibility of the Aquifer (0-25 Points)

=

Natural Susceptibility of the Well (0-50 Points)

A ranking is assigned for the Natural Susceptibility according to the point score:

Natural Susceptibility Ratings						
40-50 pts	Very High					
30 to < 40 pts	High					
20 to < 30 pts	Medium					
< 20 pts	Low					

Factors contributing to the susceptibility of the wellhead are: whether the sanitary seal is in place, protection from flooding, and if the well casing is properly grouted.

The wellhead for the Palmer Church of Christ received a **Low** susceptibility rating. The most recent sanitary survey (06/16/2004) indicates that a sanitary seal is installed on the well and the land surface is sloped away from the well, but the well is not grouted according to DEC regulations. Sanitary seals prevent potential contaminants from entering the well while sloping of the land surface and grouting help to prevent potential contaminants from traveling down the outside of the well casing.

Factors contributing to the susceptibility of the aquifer are: whether the aquifer is confined or unconfined, whether the well is completed in unconsolidated or fractured bedrock, whether wells and bore holes are penetrating the aquifer and, if applicable, the confining layer.

The Palmer Church of Christ system draws water from an unconfined aquifer over lain by silt and gravel. It received a **Very High** susceptibility rating because of its unconfined nature and the presence of other wells that penetrate the vadose zone within the protection area. Because unconfined aquifers are recharged by surface water and precipitation that migrates downward from the surface, they are susceptible to contamination from outside sources. Other wells penetration the vadose zone can also allow contaminants to travel down to the shared aquifer with precipitation and runoff.

Table 2 summarizes the Susceptibility scores and ratings for the Palmer Church of Christ system.

Table 2. Susceptibility

	Score	Rating
Susceptibility of the	5	Low
Wellhead		
Susceptibility of the	25	Very High
Aquifer		
Natural Susceptibility	30	High

Contaminant risks are derived from an evaluation of the routine sampling results of the water system and the presence of potential sources of contamination.

Contaminant risks to a drinking water source depend on the type and distribution of contaminant sources. Flow charts are used to assign a point score, and ratings are assigned in the same way as for the natural susceptibility:

Contaminant Risk Ratings							
40-50 pts	Very High						
30 to < 40 pts	High						
20 to < 30 pts	Medium						
< 20 pts	Low						

Table 3 summarizes the Contaminant Risks for each category of drinking water contaminants for the Palmer Church of Christ system.

Table 3. Contaminant Risks

Category	Score	Rating
Bacteria and Viruses	12	Low
Nitrates and/or Nitrites	16	Low
Volatile Organic Chemicals	50	Very High

Finally, an overall vulnerability score is assigned for each water system by combining each of the contaminant risk scores with the natural susceptibility score:

Vulnerability of the Drinking Water Source to Contamination (0-100 Points)

Again, rankings are assigned according to a point score:

Overall Vulnerability Ratings							
80-100 pts	Very High						
60 to < 80 pts	High						
40 to < 60 pts	Medium						
< 40 pts	Low						

Table 4 contains the overall vulnerability scores (0-100) and ratings for each of the three categories of drinking water contaminants for the Palmer Church of Christ system. Note: scores are rounded off to the nearest five.

Table 4. Overall Vulnerability

Category	Score	Rating
Bacteria and Viruses	40	Medium
Nitrates and/or Nitrites	45	Medium
Volatile Organic Chemicals	80	Very High

Bacteria and Viruses

The contaminant risk for bacteria and viruses is **Low** with septic systems and roads contributing to the risk to the drinking water well.

Coliforms (a bacteria) are found naturally in the environment and although they aren't necessarily a health threat, they are an indicator of other potentially harmful bacteria in the water, more specifically, fecal coliforms and E. coli, which only come from human and animal fecal waste. Harmful bacteria can cause diarrhea, cramps, nausea, headaches, or other symptoms (EPA, 2008). Positive samples increase the overall vulnerability of the drinking water source, indicating that the source is susceptible to bacteria and virus contamination.

Only a small amount of bacteria and viruses are required to endanger public health. Positive samples increase the overall vulnerability of the drinking water source, indicating that the source is susceptible to bacteria and virus contamination. Bacteria and viruses have not recently been detected during water sampling of the system at Palmer Church of Christ (data reviewed in April, 2008).

After combining the contaminant risk for bacteria and viruses with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Medium**.

Nitrates and Nitrites

The contaminant risk for nitrates and nitrites is **Low** with septic systems and roads contributing to the risk to the drinking water well.

The sampling history for Palmer Church of Christ well indicates that nitrates have been detected during water sampling in the last 5 years, with the highest concentration of 0.72 mg/l detected on 11/09/2006 (data reviewed in April, 2008).

After combining the contaminant risk for nitrates and nitrites with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Medium**.

Volatile Organic Chemicals

The contaminant risk for volatile organic chemicals is **Very High** with a coal mining area, septic systems, heating oil tanks, and roads contributing to the risk to the drinking water well.

The drinking water at Palmer Church of Christ has not recently been sampled for volatile organic chemicals (data reviewed in April, 2008).

After combining the contaminant risk for volatile organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Very High**.

Using the Source Water Assessment

This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of Palmer Church of Christ to protect public health. It is anticipated that Source Water Assessments will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of Palmer Church of Christ drinking water source.

REFERENCES

- Alaska Department of Commerce, Community and Economic Development (ADCCED), Accessed 2009 [WWW document]. URL: http://www.commerce.state.ak.us/dca/commdb/CF_COMDB.htm
- Freeze, R.A. and Cherry, J.A., 1979. Groundwater. Prentice-Hall, Englewood Cliffs, NJ.
- Jokela, J.B., Munter, J.A., and Evans, J.G., 1991, Ground-water resources of the Palmer-Big Lake area, Alaska: a conceptual model. Division of Geological &Geophysical Surveys Reports of Investigations 90-4, State of Alaska Department of Natural Resources, Fairbanks, AK.
- United States Environmental Protection Agency (EPA), Accessed 2008 [WWW document]. URL: http://www.epa.gov/safewater/contaminants/index.html.

APPENDIX A

Palmer Church of Christ Drinking Water Protection Area Location Map (Map A)

Public Water Well System for PWS #227563.001 Palmer Church of Christ



Legend

Class B Public Water System Well

Groundwater Protection Zones

Zone A Protection Area - Several Months Travel Time

Zone B Protection Area - 2 Years Travel Time


Data Sources:

Contaminant Sources, Public Water System Wells, Alaska Department of Environmental Conservation (ADEC)

All other data: Alaska Statewide Digital Mapping Initiative (SDMI)

Drinking Water Protection Areas based on "Alaska Drinking Water Protection Program - Guidance Manual for Class B Public Water Systems" published by ADEC

URS Corporation does not guarantee the accuracy or validity of the data provided.







Palmer Church of Christ PWS 227563.001 Appendix A Map A

0.5

APPENDIX B

Contaminant Source Inventory and Risk Ranking for Palmer Church of Christ (Tables 1-4)

Table 1

Contaminant Source Inventory for PALMER CHURCH OF CHRIST

Contaminant Source ID	CS ID tag	Zone	Map Number	Comments
E01	E01	A	C	
R02	R02	A	С	2 assumed septic systems
R08	R08	A	С	2 assumed heating oil tanks
X20	X20	A	С	1 road
E01	E01	В	С	
R02	R02	В	С	1 assumed septic systems
R08	R08	В	С	1 assumed heating oil tanks
X20	X20	В	С	1 road
	E01 R02 R08 X20 E01 R02 R08	Source ID CS ID tag E01 E01 R02 R02 R08 R08 X20 X20 E01 E01 R02 R02 R08 R08	Source ID CS ID tag Zone E01 E01 A R02 R02 A R08 R08 A X20 X20 A E01 E01 B R02 R02 B R08 R08 B	Source ID CS ID tag Zone Map Number E01 E01 A C R02 R02 A C R08 R08 A C X20 X20 A C E01 E01 B C R02 R02 B C R08 R08 B C

Contaminant Source Inventory and Risk Ranking for PALMER CHURCH OF CHRIST

PWSID 227563.001

Sources of Bacteria and Viruses

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	A	Low	С	2 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	A	Low	C	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	C	1 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	В	Low	С	1 road

Contaminant Source Inventory and Risk Ranking for PALMER CHURCH OF CHRIST

PWSID 227563.001

Sources of Nitrates/Nitrites

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	A	Low	C	2 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	A	Low	C	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	C	1 assumed septic systems
Highways and roads, paved (cement or asphalt)	X20	X20	В	Low	С	1 road

Table 4

Contaminant Source Inventory and Risk Ranking for PALMER CHURCH OF CHRIST

Sources of Volatile Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Coal mining (active or inactive?)	E01	E01	A	High	С	
Septic systems (serves one single-family home)	R02	R02	A	Low	C	2 assumed septic systems
Tanks, heating oil, residential (above ground)	R08	R08	A	Medium	C	2 assumed heating oil tanks
Highways and roads, paved (cement or asphalt)	X20	X20	A	Low	C	1 road
Coal mining (active or inactive?)	E01	E01	В	High	C	
Septic systems (serves one single-family home)	R02	R02	В	Low	C	1 assumed septic systems
Tanks, heating oil, residential (above ground)	R08	R08	В	Medium	C	1 assumed heating oil tanks
Highways and roads, paved (cement or asphalt)	X20	X20	В	Low	C	1 road

APPENDIX C

Palmer Church of Christ
Drinking Water Protection Area
and Potential and Existing Contaminant Sources
(Map C)

Public Water Well System for PWS # 227563.001 Palmer Church of Christ Showing Potential and Existing Sources of Contamination



Legend

•

Class B Public Water System Well

Groundwater Protection Zones

. .

Zone A Protection Area - Several Months Travel Time



Zone B Protection Area - 2 Years Travel Time

Data Sources:

Contaminant Sources, Public Water System Wells, Alaska Department of Environmental Conservation (ADEC)

All other data:

Alaska Statewide Digital Mapping Initiative (SDMI)

Drinking Water Protection Areas based on "Alaska Drinking Water Protection Program - Guidance Manual for Class B Public Water Systems" published by ADEC

URS Corporation does not guarantee the accuracy or validity of the data provided.







0 500 1,000 2,000

Palmer Church of Christ PWS 227563.001 Appendix C Map C