

Source Water Assessment

A Hydrogeologic Susceptibility and Vulnerability Assessment for Willow Townsite S/D Public Drinking Water System, Willow, Alaska PWSID # 220033.001

DRINKING WATER PROTECTION REPORT 1627

Alaska Department of Environmental Conservation

December, 2008

Source Water Assessment for Willow Townsite S/D Public Drinking Water System, Willow, Alaska PWSID# 220033.001

DRINKING WATER PROTECTION REPORT 1627

The Drinking Water Protection (DWP) section of the Drinking Water Program is producing Source Water Assessments in compliance with the Safe Drinking Water Act Amendments of 1996. Each assessment includes a delineation of the source water area, an inventory of potential and existing contaminant sources that may impact the water, a risk ranking for each of these contaminants, and an evaluation of the potential vulnerability of these drinking water sources.

These assessments are intended to provide public water systems owners/operators, communities, and local governments with the best available information that may be used to protect the quality of their drinking water. The assessments combine information obtained from various sources, including the U.S. Environmental Protection Agency, Alaska Department of Environmental Conservation (DEC), public water system owners/operators, and other public information sources. The results of this assessment are subject to change if additional data becomes available. It is anticipated this assessment will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of public drinking water source. If you have any additional information that may affect the results of this assessment, please contact the DWP staff at the following number: 1-866-956-7656.

CONTENTS

Willow Townsite Willow Townsite Inventory of Pote Sources	e S/D e S/D ential	Page	Vulnerability of Willow Townsite S/D Drinking WaterSystem
		TAB	LES
Table 2. Suscep Table 3. Contar	tibili ninar	tynt Risksnt Risksnerability	
		APPEN	DICES
APPENDIX	A.	Willow Townsite S/D Drinking Water	er Protection Area (Map A)
	В.	Viruses (Table 2) Contaminant Source Inventory and F (Table 3)	Villow Townsite S/D (Table 1) Risk Ranking for Willow Townsite S/D – Bacteria and Risk Ranking for Willow Townsite S/D – Nitrates/Nitrites Risk Ranking for Willow Townsite S/D – Volatile
	C.	Willow Townsite S/D Drinking Water Contaminant Sources (Map C)	er Protection Area and Potential and Existing

Source Water Assessment for Willow Townsite S/D Source of Public Drinking Water, Willow, Alaska

Drinking Water Protection Alaska Department of Environmental Conservation

EXECUTIVE SUMMARY

The public water system for Willow Townsite S/D is a Class B (transient/non-community) water system consisting of one well located on the Parks Highway in Willow, Alaska. The wellhead received a susceptibility rating of **Low** and the aquifer received a susceptibility rating of **High**. Combining these two ratings produces a Low rating for the natural susceptibility of the well. Identified potential and current sources of contaminants for Willow Townsite S/D public drinking water source include: a coal mining area, assumed septic systems, assumed heating oil tanks, roads, and a rail corridor. These identified potential and existing sources of contamination are considered as sources of bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals. Overall, the public water sources for Willow Townsite S/D received a vulnerability rating of Low for bacteria and viruses, Low for nitrates and nitrites, and **High** for volatile organic chemicals. This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of Willow Townsite S/D to protect public health.

WILLOW TOWNSITE S/D PUBLIC DRINKING WATER SYSTEM

The Willow Townsite S/D public water system is a Class B (transient/non-community) water system. The system consists of one well located on the west side of the Parks Highway in Willow, Alaska. Willow lies between Miles 60 and 80.7 of the Parks Highway, approximately 70 road miles northwest of Anchorage, and is part of the Matanuska-Susitna Borough. Temperatures in January can range from -33 to 33 degrees Fahrenheit, while in July temperatures can range from 42 to 83 degrees Fahrenheit. Willow receives between 16 and 27 inches of precipitation per year with up to 150 inches of it falling as snow. The population of Willow is 2,048 and the population of the Matanuska-Susitna Borough as a whole is 80,088 (ADCCED, 2008).

Most homes in Willow use individual wells and septic tanks, although many seasonal homes haul water and use outhouses. Electricity is provided by Matanuska Electric Association and refuse is hauled to a transfer site on Willow-Fishhook Road (ADCCED, 2008).

According to the well log, the well extends approximately 90 feet below the ground surface and is completed in an unconfined aquifer consisting of sand and gravel. This system operates continuously and serves 140 non-residents and 12 residents through one service connection.

WILLOW TOWNSITE S/D DRINKING WATER PROTECTION AREA

In order to evaluate whether a drinking water source is at risk, we must first evaluate what are the most likely pathways for surface contamination to reach the groundwater. These areas are determined by looking at the characteristics of the soil, groundwater, aquifer, and well.

The most probable area for contamination to reach the drinking water well is the drinking water protection area. The drinking water protection area is the area circling the well (the area influenced by pumping) and also the area upgradient of the well, usually forming a parabola shape. Because releases of contaminants within the protection area are most likely to impact the well, this area will serve as the focus for voluntary protection efforts.

There are many different methods for calculating the size of protection areas. Drinking Water Protection (DWP) uses a combination of two simple groundwater flow equations, the Thiem and uniform flow equations for all groundwater wells screened in unconsolidated material. The orientation of the protection zone is then drawn using a water table elevation map (if available) or a land surface elevation map of the area. The protection zone calculated by the DWP is an estimate using the available information and resources, and may differ slightly from the actual capture zone. Because of uncertainties and changing site conditions, a factor of safety is added to the protection zone to form the drinking water protection area for the well.

The parameters used to calculate the shape of this protection zone are general for the whole alluvial plain and were obtained from various United States Geological Survey (USGS) reports, area well logs, and

the Groundwater textbook by Freeze and Cherry (Freeze and Cherry, 1979).

The protection areas established for wells by the DEC are usually separated into two zones, limited by the watershed. These zones correspond to differences in the time-of-travel (TOT) of the water moving through the aquifer to the well. An analytical calculation was used to determine the size and shape of the protection area. The input parameters describing the attributes of the aquifer in this calculation were adopted from the State of Alaska Department of Water Resources (Jokela et. al., 1991).

The time-of-travel for contaminants within the water varies and is dependent on the physical and chemical characteristics of each contaminant. The following is a summary of the two protection area zones for wells and the calculated time-of-travel for each:

Table 1. Definition of Zones

Zone	Definition
A	Several months time-of-travel
В	Less than the 2 year time-of-travel

The drinking water protection area for Willow Townsite S/D was determined using an analytical calculation and includes Zones A and B (See Map A of Appendix A).

INVENTORY OF POTENTIAL AND EXISTING CONTAMINANT SOURCES

DWP has completed an inventory of potential and existing sources of contamination within the Willow Townsite S/D drinking water protection area. This inventory was completed through a search of agency records and other publicly available information. Potential sources of contamination to the drinking water aquifer include a wide range of categories and types. Potential drinking water contaminants are found within agricultural, residential, commercial, and industrial areas, but can also occur within areas that have little or no development.

For the basis of all Class B public water system assessments, the following three categories of drinking water contaminants were inventoried:

- Bacteria and viruses:
- Nitrates and/or nitrites;
- Volatile organic chemicals

The sources are displayed on Map C of Appendix C and summarized in Table 1 of Appendix B.

RANKING OF CONTAMINANT RISKS

Once the potential and existing sources of contamination have been identified, they are assigned a ranking according to what type and level of risk they represent. Ranking of contaminant risks for a "potential" or "existing" source of contamination is a function of toxicity and volumes of specific contaminants associated with that source. Rankings include:

- Low:
- Medium:
- High; and
- Very High.

Tables 2 through 4 in Appendix B contain the ranking of potential and existing sources of contamination with respect to bacteria and viruses, nitrates and/or nitrites, and volatile organic chemicals.

VULNERABILITY OF WILLOW TOWNSITE S/D DRINKING WATER SYSTEM

Vulnerability of a drinking water source to contamination is a combination of two factors:

- Natural Susceptibility; and
- Contaminant Risks.

A score for the Natural Susceptibility of the well is reached by considering the properties of the well and the aquifer.

Susceptibility of the Wellhead (0-25 Points)

+
Susceptibility of the Aquifer (0-25 Points)

=

Natural Susceptibility of the Well (0-50 Points)

A ranking is assigned for the Natural Susceptibility according to the point score:

Natural Susceptibility Ratings						
40-50 pts	Very High					
30 to < 40 pts	High					
20 to < 30 pts	Medium					
< 20 pts	Low					

Factors contributing to the susceptibility of the wellhead are: whether the sanitary seal is in place, protection from flooding, and if the well casing is properly grouted.

The wellhead for the Willow Townsite S/D received a **Low** susceptibility rating. Although no sanitary survey is available for this system, other official correspondence states that the well is capped with a sanitary seal, the land surface is appropriately sloped away from the well, and the well is grouted according to DEC regulations. Sanitary seals prevent potential contaminants from enter the well while sloping of the land surface away from the well and grouting or concrete around the wellhead help to prevent potential contaminants from traveling down the outside of the well casing.

Factors contributing to the susceptibility of the aquifer are: whether the aquifer is confined or unconfined, whether the well is completed in unconsolidated or fractured bedrock, whether wells and bore holes are penetrating the aquifer and, if applicable, the confining layer.

The Willow Townsite S/D system draws water from an unconfined aquifer consisting of sand, silt, and gravel. The aquifer received a **High** susceptibility rating because of its unconfined nature and the presence of other wells penetrating the vadose zone of the protection area. Because an unconfined aquifer is recharged by surface water and precipitation that migrates downward from the surface, it is susceptible to contamination from outside sources. Furthermore, the presence of other wells penetrating the vadose zone of the protection area can allow contaminants to travel into the shared aquifer with precipitation and runoff.

Table 2 summarizes the Susceptibility scores and ratings for the Willow Townsite S/D system.

Table 2. Susceptibility

Susceptibility of the	Score 0	Rating Low
Wellhead		
Susceptibility of the Aquifer	18	High
Natural Susceptibility	18	Low

Contaminant risks are derived from an evaluation of the routine sampling results of the water system and the presence of potential sources of contamination.

Contaminant risks to a drinking water source depend on the type and distribution of contaminant sources. Flow charts are used to assign a point score, and ratings are assigned in the same way as for the natural susceptibility:

Contaminant Risk Ratings							
40-50 pts	Very High						
30 to < 40 pts	High						
20 to < 30 pts	Medium						
< 20 pts	Low						

Table 3 summarizes the Contaminant Risks for each category of drinking water contaminants for the Willow Townsite S/D system.

Table 3. Contaminant Risks

Category	Score	Rating
Bacteria and Viruses	12	Low
Nitrates and/or Nitrites	12	Low
Volatile Organic Chemicals	50	Very High

Finally, an overall vulnerability score is assigned for each water system by combining each of the contaminant risk scores with the natural susceptibility score:

Vulnerability of the Drinking Water Source to Contamination (0-100 Points)

Again, rankings are assigned according to a point score:

Overall Vulnerability Ratings							
80-100 pts	Very High						
60 to < 80 pts	High						
40 to < 60 pts	Medium						
< 40 pts	Low						

Table 4 contains the overall vulnerability scores (0-100) and ratings for each of the three categories of drinking water contaminants for the Willow Townsite S/D system. Note: scores are rounded off to the nearest five.

Table 4. Overall Vulnerability

Category	Score	Rating
Bacteria and Viruses	30	Low
Nitrates and/or Nitrites	30	Low
Volatile Organic Chemicals	70	High

Bacteria and Viruses

The contaminant risk for bacteria and viruses is **Low** with a septic system and roads contributing to the risk to the drinking water well.

Coliforms (a bacteria) are found naturally in the environment and although they aren't necessarily a health threat, they are an indicator of other potentially harmful bacteria in the water, more specifically, fecal coliforms and E. coli, which only come from human and animal fecal waste. Harmful bacteria can cause diarrhea, cramps, nausea, headaches, or other symptoms (EPA, 2008).

Only a small amount of bacteria and viruses are required to endanger public health. Positive samples increase the overall vulnerability of the drinking water source, indicating that the source is susceptible to bacteria and virus contamination. Bacteria and viruses have not been detected during recent water sampling of the system at Willow Townsite S/D (data reviewed in April, 2008).

After combining the contaminant risk for bacteria and viruses with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Low**.

Nitrates and Nitrites

The contaminant risk for nitrates and nitrites is **Low** with a septic system and roads contributing to the risk to the drinking water well.

The sampling history for the Willow Townsite S/D well indicates that nitrates have not been detected in the water within the past five years (data reviewed in April, 2008).

After combining the contaminant risk for nitrates and nitrites with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **Low**.

Volatile Organic Chemicals

The contaminant risk for volatile organic chemicals is **Very High** with a septic system, heating oil tanks, a coal mining area, a rail corridor, and roads contributing to the risk to the drinking water well.

The drinking water at Willow Townsite S/D has not been recently sampled for volatile organic chemicals (data reviewed in April, 2008).

After combining the contaminant risk for volatile organic chemicals with the natural susceptibility of the well, the overall vulnerability of the well to contamination is **High**.

Using the Source Water Assessment

This assessment of contaminant risks can be used as a foundation for local voluntary protection efforts as well as a basis for the continuous efforts on the part of Willow Townsite S/D to protect public health. It is anticipated that Source Water Assessments will be updated every five years to reflect any changes in the vulnerability and/or susceptibility of Willow Townsite S/D drinking water source.


REFERENCES

- Alaska Department of Commerce, Community and Economic Development (ADCCED), Accessed 2008 [WWW document]. URL: http://www.commerce.state.ak.us/dca/commdb/CF_COMDB.htm
- Freeze, R.A. and Cherry, J.A., 1979. Groundwater. Prentice-Hall, Englewood Cliffs, NJ.
- Jokela, J.B., Munter, J.A., and Evans, J.G., 1991, Ground-water resources of the Palmer-Big Lake area, Alaska: a conceptual model. Division of Geological &Geophysical Surveys Reports of Investigations 90-4, State of Alaska Department of Natural Resources, Fairbanks, AK.
- United States Environmental Protection Agency (EPA), Accessed 2008 [WWW document]. URL: http://www.epa.gov/safewater/contaminants/index.html.

APPENDIX A

Willow Townsite S/D Drinking Water Protection Area Location Map (Map A)

Public Water Well System for PWS #220033.001 Willow Townsite S/D



APPENDIX B

Contaminant Source Inventory and Risk Ranking for Willow Townsite S/D (Tables 1-4)

Contaminant Source Inventory for Willow Townsite S/D

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Map Number	Comments
Coal mining (active or inactive?)	E01	E01	A	С	
Septic systems (serves one single-family home)	R02	R02	A	С	1 assumed septic system
Tanks, heating oil, residential (above ground)	R08	R08	A	С	1 assumed heating oil tank
Highways and roads, paved (cement or asphalt)	X20	X20	A	С	1 road
Coal mining (active or inactive?)	E01	E01	В	С	
Septic systems (serves one single-family home)	R02	R02	В	С	1 assumed septic system
Tanks, heating oil, residential (above ground)	R08	R08	В	С	1 assumed heating oil tank
Highways and roads, dirt/gravel	X24	X24	В	С	1 gravel road
Rail corridors	X30	X30	В	С	

Contaminant Source Inventory and Risk Ranking for Willow Townsite S/D Sources of Bacteria and Viruses

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	A	Low	С	1 assumed septic system
Highways and roads, paved (cement or asphalt)	X20	X20	A	Low	C	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	С	1 assumed septic system
Highways and roads, dirt/gravel	X24	X24	В	Low	С	1 gravel road

Contaminant Source Inventory and Risk Ranking for Willow Townsite S/D Sources of Nitrates/Nitrites

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Septic systems (serves one single-family home)	R02	R02	A	Low	C	1 assumed septic system
Highways and roads, paved (cement or asphalt)	X20	X20	A	Low	C	1 road
Septic systems (serves one single-family home)	R02	R02	В	Low	C	1 assumed septic system
Highways and roads, dirt/gravel	X24	X24	В	Low	C	1 gravel road

Contaminant Source Inventory and Risk Ranking for Willow Townsite S/D Sources of Volatile Organic Chemicals

Contaminant Source Type	Contaminant Source ID	CS ID tag	Zone	Risk Ranking for Analysis	Map Number	Comments
Coal mining (active or inactive?)	E01	E01	A	High	C	
Septic systems (serves one single-family home)	R02	R02	A	Low	C	1 assumed septic system
Tanks, heating oil, residential (above ground)	R08	R08	A	Medium	C	1 assumed heating oil tank
Highways and roads, paved (cement or asphalt)	X20	X20	A	Low	C	1 road
Coal mining (active or inactive?)	E01	E01	В	High	C	
Septic systems (serves one single-family home)	R02	R02	В	Low	C	1 assumed septic system
Tanks, heating oil, residential (above ground)	R08	R08	В	Medium	C	1 assumed heating oil tank
Highways and roads, dirt/gravel	X24	X24	В	Low	С	1 gravel road
Rail corridors	X30	X30	В	Medium	С	

APPENDIX C

Willow Townsite S/D
Drinking Water Protection Area
and Potential and Existing Contaminant Sources
(Map C)

Public Water Well System for PWS #220033.001 Willow Townsite S/D

